

TELECO Group



ULTRAcomfort

2027 EN




A PERFECT HARMONY OF SHAPES, FUNCTION AND MATERIALS

A design that perfectly blends in with any type of recreational vehicle, both with its external form and with every detail of its interior.

Continuous technical innovation resulting from years of experience, renewed and projected into the future by the enthusiasm, imagination and skills of a team of young Teleco designers.

Materials selected through strict testing and quality control to ensure that every product will retain its appearance over the course of a long working life.

These are the three simple "ingredients" that lay the foundations of our success in all European markets, and that can be found in every Teleco product.



TELECO PROVIDES OUTSTANDING TECHNICAL AND SALES ASSISTANCE



Meeting customers' expectations and solving their problems immediately is a must for Teleco.



An ever-closer relationship with the customer, who is advised at the time of purchase and assisted throughout the life cycle of the product.

While it may not always be possible to eliminate a problem at its root due to local or accidental situations, it is clear that the reaction must be quick, almost instantaneous.

1) Multilingual support service for customers to directly address minor technical questions.

2) E-mail support service for customers to turn to for more complex questions requiring a more detailed answer.

3) Teleco is continually investing in the expansion of its outstanding support network. This allows us to offer fast and qualified assistance in every country, even when on holiday. Our independent service and repair centres throughout Europe can quickly respond to all requests thanks to the constant support from Teleco, which periodically organises training and refresher courses attended by specialized technicians from all over Europe.

Independent service and repair centres throughout Europe



Ultra Comfort

ULTRA Comfort 6000 / 8000	08
ULTRA Comfort 9000M	10
ULTRA Comfort Steril-Air PRO	12

Air conditioners

Clima e-Van 3 5400H / 7400H	20
DualClima 8400H / DualClima 12500H	22
Silent 3 5900H / Silent Plus 8100H	24
Accessories for air conditioners	26

Steril Air

UV-A LED air sanitizer and purifier	28
-------------------------------------	----

Energy

Teleco Lithium Ion Series Batteries TLI PREMIUM	30
Teleco Lithium Ion Series Batteries EXTRA	31
TEB310AL / TP310A	32
TEB310ALF / TP310ALF	33
TEB310D / TP310D	34
TBooster PRO 1245	36
TBooster PRO 1225	37
Accessories for batteries and TBooster PRO	38
Inverter SINUS SI-ACT TI400/TI600/TI1000/TI1500/TI2000	40
Battery charger TBC31 PRO 30/20/250 / TBC PRO 1230 / 2417	41

Solar Panels

Black Coolflex Solar Panels TBCF 100WS -TBCF 135WS -TBCF 150WS -TBCF200WS	42
Black Flexible Solar Panels TBSF 110WS	43
Accessories	43
Black Solar Panels TBS 450W	44
Black Solar Panels TBS 110WS - TBS 185WS - TSP 145WSA - TSP 130	45
Black Portable Solar Panels TBSP 90WS	46
Power Station	46
MPPT SPC 15/1B - MPPT SPC 40/1B Solar Charge Controller	47
MPPT SPC 15/1 - MPPT SPC 20/1B - MPPT SPC 30/1B Solar Charge Controller	48
SPC10/1 - SPC20/1 PWM Solar Charge Controller	49

Connectivity

Router antennas 4G - 5G	51
Router 5G WLT58 - Wi-Fi 7	52
Router 4G WLT24EX2 - Wi-Fi	53

Automatic Sat Systems

CombiSat Wi-Fi	56
Flatsat WiFi	57
Flatsat Classic BT	58
Telesat BT	59
Flatsat Easy BT	60
Flatsat Easy Skew BT SMART	61
ActivSat SMART	62

Manual and semiautomatic Sat Systems

Voyager G3	66
------------	----



Voyager Digimatic	67
Motosat Digimatic	68
Portable Carry Sat System	69
Precision digital Satellite aligner DSF90 HD / DSF90E HD	70
Accessories - CGU2 - Motosat Kit - SPCA - SPCP /SPC64	71
CAM Modules	71
SMART TVs for Campers and Caravans	73
TEK15 W9 / TEK19E W13 / TEK22E W13	74
TEK24E W11 / TEK32E W11 / TEK40 Smart	75
12V LED televisions for Campers and Caravans	
Kit audio wireless TKB25	76
TEK 22D HEVC - TEK 22DE HEVC - TEK 22E HEVC	77
TEK 24D HEVC	77
Directional antennas DVB-T2 and DVB-T	
Teleplus X2/39U Teleplus X2/165VU Teleplus X2/110VU Teleplus X2/51VU	79
Teleplus 3G	80
Teleplus	81
Directional antennas DVB-T2 and DVB-T	
Weekend Super	81
Yachting 11	81
Walkie 22	81
WING	82
WING 11	83
WING 22	83
WING LAN 11 - Teleco Connect	84
Control center via smartphone	
Teleco Hub	85
Multimedia Systems	
T-AMM10DAB Android Multimedia Monitor	86
T-CPA 70 DAB CarPlay	87
Video cameras and Monitors	
TRC14CCD - TRC135 CCD - TRCL CMOS	88
TP7 HR/2 - TP7 HR/4	88
Generators	89
TIG6000B	92
TIG6000G	93
TIG3100B	94
TIG3100G	95
TIG3000D	96
Energy 2510 G	98
Energy 2510 B	99
Accessories for generators 230 Vac	100
EcoEnergy TG480 / TG480 MEF / TG600 MEF	102
Accessories for EcoEnergy	104



ULTRAcomfort

**A WORLD FIRST: THE ULTRA
COMFORT AIRCONDITIONER
THE BEGINNING OF A
NEW ERA.**



TELECO



**GERMAN
INNO
VATION
AWARD '24
WINNER**



WINNER 2026

ULTRA Comfort 6000-8000 CONDIZIONATORE

The ideal solution for Vans, Vans with pop-up roof
and Semi-Integrated Motorhomes

DLICATO STELLANTIS



2026

DLICATO STELLANTIS

- No overhead weight, which saves space on the roof
- Preserves the brightness of a skylight
- Completely invisible compression unit
- Discreet, built-in inner diffuser
- No more diffuser in the corridor
- Quiet and powerful with minimal power consumption
- Fully reversible for both cooling and heating via heat pump
- Enables the installation of an air conditioner on vehicles with pop-up roof
- 230V power supply
- Dual function: cooling and heating (heat pump*)
- Three ventilation speeds + automatic mode
- Low power consumption (less than 3A for UltraComfort 6000 model)
- Weight: 28 - 34 kg
- Diffuser grids adjustable both vertically and horizontally
- Display with temperature indication
- Easy control of the air conditioner via remote control
- Recommended vehicle length: 5 - 6,5 m (for mod. 6000) and 6 - 7 m (for mod. 8000)
- Option Wi-Fi
- Option Steril Air PRO

*For outdoor temperature above +5 °C

PATENT PENDING




Available models

TECHNICAL SPECIFICATIONS

	ULTRA COMFORT 6000	ULTRA COMFORT 8000
Power Supply	230V, 50Hz ~	230V, 50Hz ~
Cooling capacity*	6000Btu/h 1760W	7500Btu/h 2200W
Heating capacity	5700Btu/h 1670W	7200Btu/h 2100W
Current absorption	2,9A	4,2A
IR Remote Control	yes	yes
Temperature setpoint range	16÷31°C	16÷31°C
Indoor fan speeds	3 + Auto	3 + Auto
Internal air flow	360m3/h	360m3/h
Refrigerant type & max quantity	R134a / 600g	R134a / 650g
Teleco Inverter required	TI 1500 SI-ACT	TI 2000 SI-ACT
Certifications	CE / R10	CE / R10
Weight	28 kg	34 kg

*Heating performance gradually decreases when the outside temperature falls below +15°C.



The ULTRA COMFORT 6000 is made up of 2 units:

- 1) The internal unit fits into the dashboard inside the vehicle
- 2) External Unit, made of 2 parts connected by pipes, mounted behind the bumper of the Vehicle

The two parts are connected by flexible hoses via rapid fittings

The refrigerant gas is already loaded into the air conditioner and distributed throughout all parts, including the watertight connection pipes

The air conditioner has a dual function: Cooling and Heating (Heat Pump).



Compatible with
WiFi
CI-BUS
Teleco HUB,
with ICLE interface
(optional, not included)



No bulky device
on the roof



Suitable for pop-up
roof-van



Keep the rooflight,
more light inside



Silent



Heat pump



No compressor
noise



No cold air diffuser
in the corridor



Dashboard
diffuser



Dog friendly



Option

STERIL-AIR PRO Option



KAMI 6000 - 8000

Optional: Installation kit for
Ultra Comfort 6000 on
vehicles with IVECO engine



Original
TELECO

* Not included
because
already in the
vehicle

KIT KD26

Option: Installation kit for
DUCATO 2026 models



PLEASE NOTE:

Ultra Comfort 6000 and Ultra Comfort 8000 are compatible with DUCATO chassis from 2021 onwards. For vehicles with X250 chassis and IVECO engines from 2014 to 2021, the KAMI 6000 installation kit must be purchased as an option.

ULTRAcomfort 9000M CONDIZIONATORE

The ideal solution for Vans, Vans with pop-up roof
and Semi-Integrated Motorhomes



Mercedes *SPRINTER*

- No overhead weight, which saves space on the roof
- Preserves the brightness of a skylight
- Completely invisible compression unit
- Discreet, built-in inner diffuser
- No more diffuser in the corridor
- Quiet and powerful with minimal power consumption
- Fully reversible for both cooling and heating via heat pump
- Enables the installation of an air conditioner on vehicles with pop-up roof
- 230V power supply
- Dual function: cooling and heating (heat pump*)
- Three ventilation speeds + automatic mode
- Low power consumption
- Weight: 28 - 34 kg
- Diffuser grids adjustable
- Display with temperature indication
- Easy control of the air conditioner via remote control
- Recommended vehicle length: 6 - 7,5 m
- **Option Wi-Fi**
- **Option Steril Air PRO**

* For outdoor temperature above +5 °C



ULTRA Comfort 9000M

TECHNICAL SPECIFICATIONS

	ULTRA COMFORT 9000 MV	ULTRA COMFORT 9000 MS
For	Rear-wheel drive	Front-wheel drive
Power Supply	230V, 50Hz ~	230V, 50Hz ~
Cooling capacity*	7900Btu/h 2310W	7900Btu/h 2310W
Heating capacity*	7560Btu/h 2205 W	7560Btu/h 2205 W
Current absorption	4,4A	4,4A
IR Remote Control	yes	yes
Temperature setpoint range	16÷31°C	16÷31°C
Indoor fan speeds	3 + Auto	3 + Auto
Internal air flow	360m3/h	360m3/h
Refrigerant type & max quantity	R1234yf / 700g	R1234yf / 700g
Teleco Inverter required	TI 2000 SI-ACT	TI 2000 SI-ACT
Certifications	CE / R10	CE / R10
Weight	34 kg	34 kg

*Heating performance gradually decreases when the outside temperature falls below +15°C.



The ULTRA COMFORT 9000 is made up of 2 units:

- 1) The internal unit fits into the dashboard inside the vehicle
- 2) External Unit, made of 2 parts connected by pipes, mounted behind the bumper of the Vehicle

The two parts are connected by flexible hoses via rapid fittings

The refrigerant gas is already loaded into the air conditioner and distributed throughout all parts, including the watertight connection pipes

The air conditioner has a dual function: Cooling and Heating (Heat Pump).



Compatible with
WiFi
CI-BUS
Teleco HUB,
with ICLE interface
(optional, not included)



Suitable for pop-up
roof-van



No bulky device
on the roof



Keep the rooflight,
more light inside



Silent



Heat pump



No compressor noise



No cold air diffuser
in the corridor



Dashboard diffuser




Dog friendly




Option

STERIL-AIR PRO

Option



Installation on
FRONT-WHEEL-DRIVE Model
(MS version)



Installation on
REAR-WHEEL-DRIVE Model
(MV version)

ULTRAcomfort

STERIL-AIR PRO



DUCATO STELLANTIS



Mercedes **SPRINTER**

STERIL-AIR PRO

Our most innovative air conditioner, now equipped with a UV-A LED air sanitizer and purifier

UV-A LED technology with photocatalysis, which is highly efficient in removing:

- Organic contaminants
- Bad odours
- Viruses
- Bacteria
- Formaldehyde
- Benzenes

ADVANTAGES OF A UV-LED DEVICE



SAFE

Thanks to LED UV-A technology, the device is completely safe and can be used where people or animals are present



24H SANITIZATION

Can be used 24/7, ensuring continuous air sanitization.



ENERGY EFFICIENCY

Has low energy consumption, thus ensuring optimal energy efficiency. Moreover, unlike slower mercury lamps, it comes on instantaneously..



NO CHEMICAL SUBSTANCES USED

Compared to other technologies like ozone and mercury lamps, UV-A LEDs are much safer for people and have no environmental impact as no chemical substances are used.



HIGH PERCENTAGE OF VIRUSES AND BACTERIA ELIMINATED (SARS COV-2 included))

Has been certified by accredited laboratories.



LONGER LASTING

Another key advantage of UV LEDs is that they last longer than mercury lamps.

Average UV LED lifespan: 20.000–30.000 hours

Average mercury lamp lifespan: 2.000–10.000 hours.

The photocatalysis system and UV-A LEDs proved effective in tests on SARSCoV-2 (covid 19). After 30 minutes, they reduced the viral load by 99,998%.


UV FILTERS

The function of UV filters are to destroy many harmful particles for our lungs. Many microorganisms which are normally found in the air and which we are unable to see with the naked eye are eliminated.

Remember that UV is just an acronym that stands for **Ultra Violet**.


Consequently, the UV purifier is a purifier that emits radiation in the Ultraviolet spectrum.

The figure shows the spectrum of light, including UV radiations. These are invisible to the human eye, which only perceives rays in a certain wave range (400 to 780nm).



UV-A LED: PROTECTION, SUSTAINABILITY AND EFFECTIVENESS

UV radiation, emitted by the sun, if properly dosed in intensity and wavelength, can be used in many applications in our daily lives. When applied to LED lamps, UV technology can be very useful in various sectors, and is used differently depending on intensity and wavelength (UV-A, UV-B, UV-C). In particular, it can be very effective in reducing the amount of bacteria, the virulence of harmful organisms and the presence of pathogens, as well as in the breakdown of volatile organic compounds (VOC), thus reducing odours in general.



STERIL-AIR PRO is also compatible with the following models of roof-mounted air conditioners



SILENT 3 5900H

SILENT 3 8100H

DUALCLIMA 8400H

DUALCLIMA 12500H

AIR CONDITIONER

When the summer is torrid, the heat is suffocating and humidity prevents you from sleeping at night, there's no need to worry, because Telair will look after you. You don't have to miss out on holidays in the south of Europe just because heat and mugginess might make your stay unbearable. A Telair air conditioner will make your days pleasurable and relaxing. A sense of well-being will accompany you throughout your holiday, the system constantly cooling and drying the air inside your motorhome or caravan. Telair's flat and aerodynamic roof-mounted air conditioners are the perfect solution, taking up minimal space inside the vehicle. Modern, innovative design makes installation of the unit on the roof quick and easy, as uses the standard 40 x 40 cm roof-light opening, without affecting the aerodynamics of the vehicle.



The range of E-Van, Dual Clima and Silent air conditioners, built with 4 different cooling levels, can be installed on any type of caravan or motorhome, from small (4 or 5 m) to large (8 or 10 m). The choice of the correct model to install is very simple. Just check the length of your vehicle and match it to the following table:



e-Van3 5400H	4 - 6 m
Silent3 5900H	5 - 6,5 m
e-Van3 7400H	5 - 7 m
Silent3 8100H	6 - 7,5 m
DualClima 8400H	6,5 - 8 m
DualClima 12500H	8 - 10 m





AIR DIFFUSERS

There are two models of air diffusers for the vehicle interior:

DualClima



Dual Clima diffuser, modern design and super-flat (just 4.9 cm thick). Fitted with an efficient and silent system for distributing cold (or hot) air that can reach any part of the vehicle. The two main outputs are connected to an adjustable flow separator that allows air to be distributed in two directions (Front – Rear) or allows the flow to be adjusted gradually until it is all concentrated in just one direction. Each of the two outputs can also be oriented from left to right and from up to down in order to maximise comfort. Fitted with 2 honeycomb dust filters that can easily be extracted and washed under running water. An LED display showing room temperature and 2 LED lights indicating the status (cooling or heating) of the air conditioner will help you control it at all times. Infrared remote control with timer (ON-OFF) and large display. Ambient lighting with two LED bars that can be activated with the remote control.

Also available with Wi-Fi option.

Wi-Fi 



Silent 3 clima e-Van 3



Silent 3 and e-Van 3 Diffuser, small, compact with cold air outlet that can be aimed in two directions (forwards and rearwards) or focused in one direction. Easy to clean, with two dust filters that can be removed effortlessly and washed in running water whenever necessary. Fitted with an LED display, a room temperature indicator and an infrared remote control with timer.

Also available with Wi-Fi option.

Wi-Fi 






HEAT PUMP

All Dual Clima and Silent Plus air conditioners are also equipped with a Heat Pump heating system. So besides being used to cool the vehicle, they can also be used as a low-cost heating system in the off-season.

Heat pump heating has some major advantages:

- It consumes very little, with 900W of consumption it provides up to 2.4 kW of heat
- It removes moisture from the air, which benefits your health
- It is fast and switches from hot to cold automatically to maintain a constant pre-set temperature
- It works properly down to about 4°C


ULTRA Comfort
ULTRA Comfort
clima e-Van 3

	ULTRA COMFORT		ULTRA COMFORT		clima e-Van 3
			REAR-WHEEL DRIVE	FRONT-WHEEL DRIVE	
TECHNICAL SPECIFICATIONS	ULTRA COMFORT 6000	ULTRA COMFORT 8000	ULTRA COMFORT 9000 MV	ULTRA COMFORT 9000 MS	CLIMA e-Van 3 5400H
Cooling power	6000 BTU 1,76 kW 	7500 BTU 2,2 kW 	7900 BTU 2,3 kW 	7900 BTU 2,3 kW 	5.800 BTU 1,7 kW 
Heat pump heating power*	5.700 BTU 1,67 kW 	7.200 BTU 2,1 kW 	7.560 BTU 2,2 kW 	7.560 BTU 2,2 kW 	5.500 BTU 1,6 kW 
Fan speed	3 + AUTO	3 + AUTO	3 + AUTO	3 + AUTO	3 + AUTO
Power supply	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz
Average absorbed current	2,9 A  2,8 A 	4,2 A  4,1 A 	4,4 A  4,1 A 	4,4 A  4,1 A 	2,9 A  2,8 A 
Starting current	15 A (150 msec.)	18 A (150 msec.)	18 A (150 msec.)	18 A (150 msec.)	15 A (100 msec.)
Absorbed power	680 W 640 W	1100 W 1000 W	1100 W 1000 W	1100 W 1000 W	660 W 640 W
Recommended inverter	TI 1500 SI ACT	TI 2000 SI ACT	TI 2000 SI ACT	TI 2000 SI ACT	TI 1500 SI ACT
Max air flow	360 m³/h	360 m³/h	360 m³/h	360 m³/h	300 m³/h
Weight	28 Kg.	34 Kg.	34 Kg.	34 Kg.	30 Kg.
Dimensions	–	–	–	–	23,2x71x61,9 cm ↑ → ↗
Air diffuser height	–	–	–	–	4,2x45x45 cm. ↑ → ↗
STERIL-AIR PRO Option	●	●	●	●	–
Remote Control  Timer	●	●	●	●	●
Wi-Fi  Compatible with  	●	●	●	●	●
CI-BUS 	●	●	●	●	●
Suitable for vehicles 	5 - 6,5 m	6 - 7 m	6 - 7,5 m	6 - 7,5 m	4 - 6 m

*Heating performance gradually decreases when the outside temperature falls below +15°C.




CLIMA e-Van 3 7400H

SILENT 3 5900H

SILENT 3 8100H

DUALCLIMA 8400H

DUALCLIMA 12500H



clima e-Van 3

Silent 3

Silent 3

DualClima

DualClima

CLIMA e-Van 3
7400HSILENT 3
5900HSILENT 3
8100HDUALCLIMA
8400HDUALCLIMA
12500H7.200 BTU
2,1 kW5.900 BTU
1,73 kW8.100 BTU
2,37 kW8.500 BTU
2,50 kW10.800 BTU
3,17 kW6.800 BTU
2,0 kW5.600 BTU
1,64 kW8.000 BTU
2,30 kW8.400 BTU
2,46 kW10.500 BTU
3,08 kW

3 + AUTO

3 + AUTO

3 + AUTO

3 + AUTO

3 + AUTO

230 V 50 Hz

230 V 50 Hz

230 V 50 Hz

230 V 50 Hz

230 V 50 Hz

4,1 A
4,0 A2,9 A
2,8 A4,8 A
4,3 A4,3 A
4,1 A6,1 A
5,9 A19 A
(150 msec.)15 A
(150 msec.)18 A
(150 msec.)18 A
(150 msec.)29 A
(150 msec.)950 W
920 W680 W
640 W1100 W
1000 W990 W
950 W1.400 W
1.350 W

TI 2000 SI ACT

TI 1500 SI ACT

TI 2000 SI ACT

TI 2000 SI ACT

TI 2000 SI ACT

300 m³/h

400 m³/h

450 m³/h

480 m³/h

480 m³/h

31 Kg.

34 Kg.

36 Kg.

36 Kg.

39 Kg.

23,2x71x61,9 cm
↑ → ↗23,9x98x65 cm
↑ → ↗23,9x98x65 cm
↑ → ↗23,9x98x65 cm
↑ → ↗23,9x98x65 cm
↑ → ↗4,2x45x45 cm.
↑ → ↗4,2x45x45 cm.
↑ → ↗4,2x45x45 cm.
↑ → ↗5,4x60x52 cm.
↑ → ↗5,4x60x52 cm.
↑ → ↗

-

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

•

5 - 7 m

5 - 6,5 m

6 - 7,5 m

6,5 - 8 m

8 - 10 m

clima e-Van 3

THE SMALLEST ROOF-MOUNTED AIR CONDITIONER ON THE MARKET

Just 71cm long and 23 cm high



 GAS R32

 230 volt

5400H

 1,7 kW (5.800 BTU)

 1,6 kW (5.500 BTU)

 TIMER



Wi-Fi OPTION available

7400H

 2100 W (7.200 BTU)

 2000 W (6.800 BTU)

 TIMER

clima e-Van 3 5400H / 7400H

AUTOMATIC AIR CONDITIONERS WITH HEAT PUMP

Specially designed for Camper Vans, the ideal solution for installation on small roofs without having to remove the skylight.

Silent, light and easy to install, it is secured to the roof both with the usual 40x40 cm roof-light opening and with a smaller 36x36 cm hole.

Featuring cutting-edge technology, its design exploits all the latest resources to offer an Ecologically Clean product.

An R32 gas refrigerant has been used as it has the lowest Global Warming Potential (GWP 675) that is currently found on air conditioners for vehicles, with a 70% reduction in environmental pollution power, compared to gases that have been used to date.

Two models are available with different refrigerating powers; both feature a heat pump. Cold, Hot and Automatic functions can be selected via the remote control, Timer function.


The CLIMA e-VAN 3 5400H model has been designed for low consumption. It can also be connected to a battery through a pure sine wave inverter of minimum 1500W (at full capacity) for use in moving vehicles.

The small internal diffuser with its modern design is just approximately 4.2 cm thick and can easily be installed thanks to its small size. Equipped with a multi-function blue display and LED lights that can be switched on/off via the remote control.



LED TORCH

TIMER



5400H
4 - 6 m

7400H
5 - 7 m



Extra-flat diffuser with sloping profile on all 2 sides. Adjustable front and rear air outlets.



Technical specifications	CLIMA e-Van 3 5400H	CLIMA e-Van 3 7400H
Cooling power	5.800 BTU / 1,7 kW	7.200 BTU / 2,1 kW
Heating power*	5.500 BTU / 1,6 kW	6.800 BTU / 2,0 kW
Ventilation speeds	3 + AUTO	3 + AUTO
Power supply	230 V - 50 Hz	230 V - 50 Hz
Average absorbed current	2,9 A ❄️ 2,8 A 🔥	4,1 A ❄️ 4,0 A 🔥
Starting current	15 A (150 ms)	19 A (150 ms)
Power consumption	660 W ❄️ 640 W 🔥	950 W ❄️ 920 W 🔥
INVERTER recommended	TI 1500 SI ACT	TI 2000 SI ACT
Maximum air flow rate	300 m³/h	300 m³/h
Weight	30 Kg.	31 Kg.
Roof unit dimensions	23,2x71x61,9 cm ↗ ↘ ↙ ↚	23,2x71x61,9 cm ↗ ↘ ↙ ↚
Air diffuser dimensions	4,2x45x45 cm. ↗ ↘ ↙ ↚	4,2x45x45 cm. ↗ ↘ ↙ ↚
Wi-Fi option*	✓	✓
BLACK color option	-	✓

Compatible with
 Google Assistant
 alexa



Compatible with
 Wi-Fi
 CI-BUS
 Teleco HUB,
 with ICW interface
 (optional, not included)

*When the outdoor temperature drops below 15 °C, the heating capacity gradually decreases

DualClima

12500H / 8400H



GAS R32



230 volt

8400H GAS R32



2,5 KW (8.500 BTU)



2,46 KW (8.400 BTU)



TROPICAL TILL 55°C



TIMER

12500H GAS R32



3,10 KW (10.800 BTU)



3,08 KW (10.500 BTU)



SOFT START



TIMER



DualClima 8400H / 12500H

AUTOMATIC AIR CONDITIONERS WITH HEAT PUMP

DUALCLIMA monoblock air conditioner specially designed to be installed on the roofs of medium-to-large campers and caravans. Special care has been taken to ensure LOW NOISE both inside and outside.

- **HEAT PUMP** High-efficiency heat pump heating supplies more than double the heating power for the power supplied. The heat pump is effective for outside temperatures down to 4°C; below this temperature its efficiency is considerably reduced.
- **AUTOMATIC CONTROL**
By activating the AUTO function, the air conditioner selects the most suitable ventilation speed and the cooling or heating function automatically.
- **REMOTE CONTROL** with a programmable timer and ON/OFF Switch for the Diffuser Light
- Anti-freeze protection PROBES
- **INTERNAL FILTERS** – can be changed and washed
- Suitable for roofs 30 - 70 mm thick



LED TORCH

TIMER



8400H


6,5 - 8 m

12500H

8 - 10 m



Extra-flat diffuser with sloping profile on all 4 sides. Direction-adjustable front and rear air outlets (horizontal and vertical).



Technical specifications	DUALCLIMA 12500H	DUALCLIMA 8400H
Cooling power	10.800 BTU / 3,17 kW	8.500 BTU / 2,50 kW
Heating power*	10.500 BTU / 3,08 kW	8.400 BTU / 2,46 kW
Ventilation speeds	3 + AUTO	3 + AUTO
Power supply	230 V - 50 Hz	230 V - 50 Hz
Average absorbed current	6,1 A ❄️ 5,9 A 🔥	4,3 A ❄️ 4,1 A 🔥
Starting current	29 A (150 m sec.)	18 A (150 m sec.)
Power consumption	1400 W ❄️ 1350 W 🔥	990 W ❄️ 950 W 🔥
INVERTER recommended	TI 2000 SI ACT	TI 2000 SI ACT
Maximum air flow rate	480 m3/h	480 m3/h
Weight	39 Kg.	36 Kg.
Roof unit dimensions	23,9x98x65 cm ↗ ↘ ↙ ↚	23,9x98x65 cm ↗ ↘ ↙ ↚
Air diffuser dimensions	4,9x52x60 cm ↗ ↘ ↙ ↚	4,9x52x60 cm ↗ ↘ ↙ ↚
Wi-Fi option*	✓	✓
BLACK color option	-	✓
Option STERIL AIR PRO	✓	✓

*When the outdoor temperature drops below 15 °C, the heating capacity gradually decreases



Compatible with
Wi-Fi
CIBUS
Teleco HUB,
with ICW interface
(optional, not included)

STERIL-AIR PRO

Optional

Silent 3



 GAS R32

 230 volt



5900H

 1,73 kW (5.900 BTU)

 1,64 kW (5.600 BTU)

 TIMER

8100H

 2,37 kW (8.100 BTU)

 2,30 kW (8.000 BTU)

 TIMER



Wi-Fi OPTION
available

Silent 3 5900H / 8100H

AUTOMATIC AIR CONDITIONERS WITH HEAT PUMP

Silent, light, easy to install and technologically advanced, these air conditioners are designed to make full use of all the latest resources to provide an ecologically clean product.

An R32 gas coolant has been used as it has the lowest Global Warming Potential (GWP 675) currently found on vehicle air conditioners and reduces environmental pollution potential by 70% compared to the gases that have been used to date.

Two models with different refrigerating powers are available; both are equipped with a heat pump. Cooling, Heating, Ventilation and Automatic modes can be selected via the remote control. A timer function is also provided.


The Silent 3 5900H model has been designed for low consumption. It can also be connected to a battery via a pure sine wave inverter with a minimum rating of 1500 W (operation at full capacity) for use when the vehicle is on the move.



The small internal diffuser features modern design, is just 4.2 cm thick and its compact size means it can be installed easily. Features include a multi-function blue display and LED lights that can easily be switched on-off via the remote control.



LED TORCH

TIMER





Technical specifications	Silent 3 5900H	Silent 3 8100H
Cooling power	5.900 BTU / 1,73 kW	8.100 BTU / 2,37 kW
Heating power*	5.600 BTU / 1,64 kW	8.000 BTU / 2,30 kW
Ventilation speeds	3 + AUTO	3 + AUTO
Power supply	230 V - 50 Hz sinusoidal	230 V - 50 Hz sinusoidal
Average absorbed current	2,9 A ❄️ 2,8 A 🔥	4,8 A ❄️ 4,3 A 🔥
Starting current	15 A (0,15 sec.)	18 A (0,15 sec.)
Power consumption	680 W ❄️ 640 W 🔥	1100 W ❄️ 1000 W 🔥
INVERTER recommended	TI 1500 SI ACT	TI 2000 SI ACT
Maximum air flow rate	400 m³/h	450 m³/h
Weight	34 Kg.	36 Kg.
Roof unit dimensions	23,9x98x65 cm ↗ ↘ ↙ ↚	23,9x98x65 cm ↗ ↘ ↙ ↚
Air diffuser dimensions	4,2x45x45 cm. ↗ ↘ ↙ ↚	4,2x45x45 cm. ↗ ↘ ↙ ↚
Wi-Fi option*	✓	✓
BLACK color option		✓
Opzione STERIL AIR PRO	✓	✓

*When the outdoor temperature drops below 15 °C, the heating capacity gradually decreases



Compatible with
WiFi
CIBUS
Teleco HUB,
with ICW interface
(optional, not included)

STERIL-AIR PRO
Optional

Accessories for Air Conditioners



Air conditioner adapter for van roof




15 mm foam for mod. e-Van




25mm foam for mod. e-Van



20 mm foam for mod. DualClima and Silent 3



Air filters for Silent Plus / e-Van models



Air filters for DualClima models



Air filters for Silent 3 / e-Van3 models



Thick frame for A/C installation on vehicles with a thin roof



CPS
Protective Cover for Silent/Dualclima Air Conditioners



CPE
Protective cover for e-Van 3 air conditioners



CAMPER KIT e-Van
for roof thickness > 40 mm




ICLE interface



ICL interface



ICW interface for Wi-Fi



Air filters for Ultra Comfort models




STERIL AIR UV-A

UV-A LED air sanitizer and purifier

Improve the quality of the air you breathe in all the environments you live in every day.

UV-A LED technology with photocatalysis, which is highly efficient in removing:

- Organic contaminants
- Bad odours
- Viruses
- Bacteria
- Formaldehyde
- Benzenes



ADVANTAGES OF A UV-LED DEVICE



SAFE

Thanks to LED UV-A technology, the device is completely safe and can be used where people or animals are present



24H SANITIZATION

Can be used 24/7, ensuring continuous air sanitization.



ENERGY EFFICIENCY

Has low energy consumption, thus ensuring optimal energy efficiency. Moreover, unlike slower mercury lamps, it comes on instantaneously..



NO CHEMICAL SUBSTANCES USED

Compared to other technologies like ozone and mercury lamps, UV-A LEDs are much safer for people and have no environmental impact as no chemical substances are used.



HIGH PERCENTAGE OF VIRUSES AND BACTERIA ELIMINATED (SARS COV-2 included))

Has been certified by accredited laboratories.



LONGER LASTING

Another key advantage of UV LEDs is that they last longer than mercury lamps. Average UV LED lifespan: 20.000–30.000 hours
Average mercury lamp lifespan: 2.000–10.000 hours.

The photocatalysis system and UV-A LEDs proved effective in tests on SARSCoV-2 (covid 19). After 30 minutes it reduces the viral load by 99.998%.


UV FILTERS

The function of UV filters are to destroy many harmful particles for our lungs. Many microorganisms which are normally found in the air and which we are unable to see with the naked eye are eliminated.

Remember that UV is just an acronym that stands for **Ultra Violet**.

Consequently, the UV purifier is a purifier that emits radiation in the Ultraviolet spectrum.

The figure shows the spectrum of light, including UV radiations. These are invisible to the human eye, which only perceives rays in a certain wave range (400 to 780nm).




UV-A LED: PROTECTION, SUSTAINABILITY AND EFFECTIVENESS

UV radiation, emitted by the sun, if properly dosed in intensity and wavelength, can be used in many applications in our daily lives.

When applied to LED lamps, UV technology can be very useful in various sectors, and is used differently depending on intensity and wavelength (UV-A, UV-B, UV-C). In particular, it can be very effective in reducing the amount of bacteria, the virulence of harmful organisms and the presence of pathogens, as well as in the breakdown of volatile organic compounds (VOC), thus reducing odours in general.



ENERGY



It is easy to manage the power in your motorhome with TELECO's complete range of products:

- Control unit with touchscreen panel to control the entire motorhome
- LifePO4 smart lithium batteries
- Solar panels with MPPT regulators that can be controlled via smartphone.
- TBooster, an intelligent device for charging batteries while driving
- Sine-wave inverter for powering 230 V appliances via the lithium battery

PREMIUM

lithium batteries

LITHIUM ION BATTERIES (LIFEPO4)

3 POWER POINTS, ONE SINGLE (DIN)

12/104 DIN - 12/135 DIN - 12/150 DIN




WIRELESS)))

Innovative Teleco batteries with Lithium-ion technology, specifically designed for leisure vehicles.

Compared to traditional batteries they have numerous advantages:

- They are up to 70% lighter and smaller
- They charge much faster, and can be fully charged in less than an hour
- They are extremely long-lasting. They can be recharged up to 5000 times, practically 10 times more than a traditional lead battery
- They can be fitted in any position
- They allow load starts with extremely high inrush currents
- They are safe thanks to utilisation of Lithium Iron Phosphate (LiFePO4 or LFP) technology
- They are ecological because they use materials of low environmental impact: they do not use lead or other harmful materials as per the ROHS directive.



TLI PREMIUM Range

TLI PREMIUM (professional) batteries stand out compared to other lithium batteries on the market because of their high energy density: weight and size being equal, they can store much higher quantities of energy. TLI PREMIUM batteries incorporate a sophisticated Battery Management System (BMS) that controls the voltage of each cell during both during charging/discharging, thus increasing its lifespan. The BMS also ensures protection against failure in the event of high temperatures, overloads and excessive discharging. It's possible to connect up to 2 batteries in series and up to 3 in parallel (batteries with the same capacity).

Key BMS features:

- Integrated CANBUS, CI BUS and Wireless communications
- Integrated solid-state relay for safety disconnection
- Autosleep mode and wakeup key
- Diagnostics and error log
- Control panel (optional) with charge indicator and input/output control from storage mode

The BMS also ensures protection against failure in the event of high temperatures, overloads and excessive discharging.

Guaranteed quality:

- Quality control performed at every single stage of production
- Latest-generation components

In-App low battery alert



TECHNICAL SPECIFICATIONS

Model	TLI PREMIUM 12/104 DIN	TLI PREMIUM 12/135 DIN	TLI PREMIUM 12/150 DIN	TLI PREMIUM 12/200
Rated voltage	12,8V	12,8V	12,8V	12,8V
Maximum capacity	104 Ah	135 Ah	150 Ah	200 Ah
Energy	1280 Wh	1728 Wh	1920 Wh	2560 Wh
Recommended discharge current @ 25°C	20 Amp	24 Amp	30 Amp	40 Amp
Max continuous discharge current @ 25°C	100 Amp	135 Amp	150 Amp	200 Amp
Recommended charging current @ 25°C	20 Amp	24 Amp	30 Amp	40 Amp
Max charging current @ 25°C	100 Amp	135 Amp	150 Amp	200 Amp
Duration	2000 cycles @ 80% DOD @25°C with 80% residual energy			
Service life	5/7 years	5/7 years	5/7 years	5/7 years
Charging voltage	14,4 - 14,6 V	14,4 - 14,6 V	14,4 - 14,6 V	14,4 - 14,6 V
Weight	10,5 Kg	13 Kg	14,5 Kg	23,3 Kg
Dimensions [mm]	355x175xH190 DIN L5	355x175xH190 DIN L5	355x175xH190 DIN L5	521x238xH218
Terminal	SAE automotive	SAE automotive	SAE automotive	M8
Temperature, during charging	0 °C / +45 °C	0 °C / +45 °C	0 °C / +45 °C	0 °C / +45 °C
Temperature, during discharging	-20 °C / +60 °C	-20 °C / +60 °C	-20 °C / +60 °C	-20 °C / +60 °C
Temperature, during prolonged storage	-10 °C / +50 °C	-10 °C / +50 °C	-10 °C / +50 °C	-10 °C / +50 °C
Certifications	IEC62133-2, EN55014-1, EN55014-2, UN38.3, RoHs, CE Conformity, UN ECE R10			

TCP – OLED control panel (opcional)

Dimensions [mm] (Compatible with Berker frames)	59,5 x 59,5 x H13
Displayed information	Voltage, Current, Power, State of charge, Alarms
Supplied	Ethernet cable (5 m)

EXTRA
lithium batteries



Technical specifications	TLI Extra 12/160
Rated voltage	12,8V
Capacity	100 Ah
Energy	2048 Wh
Recommended discharge current @ 25°C	32 Amp
Max continuous discharge current @ 25°C	100 Amp
Recommended charging current @ 25°C	32 Amp
Max charging current @ 25°C	100 Amp
Duration	2000 cycles @ 80% DOD @25°C with residual energy 80%
Service life	5/7 years
Charging voltage	14,4 - 14,6 V
Weight	20,5 Kg
Dimensions [mm]	485 x 170 x H241
Terminal	M8
Temperature, during charging	0 °C / +45 °C
Temperature, during discharging	-20 °C / +60 °C
Temperature, during prolonged storage	-10 °C / +50 °C
Certifications	IEC62133-2, EN55014-1, EN55014-2, UN38.3, RoHs, CE Conformity, UN ECE R10

TEB310AL



Electronic control unit to control a camper with battery charger, connectors and fuses



The TEB310AL is an analog/digital control unit fitted with a 230 Vac / 12 Vdc battery charger, designed to power all the 12 Vdc electrical appliances in a motorhome.

The electronic control unit is fitted with a digital control module which has the following functions:

- Charging of all connected batteries via the 230 V AC mains supply: service battery (up to 20 Ah) and starter battery (6 A max.)
- Distribution of current to connected 12 V loads
- Fuse protection for connected 12 V loads
- Monitoring of battery voltage and charge level (LITHIUM only) via the TP310A panel
- Recharging of the service battery as well as the starter battery while driving (via the alternator)
- Charging battery via an external solar panel
- Disconnection of all loads from the battery when the vehicle is in storage, by simply operating the dedicated switch.
- Charging selector for 4 battery types: LITHIUM, AGM, ACID, GEL
- CI BUS connector that connects the lithium batteries (of the latest generation) to the TP310A panel to monitor their charge level
- Automatic cut-off device for electrical loads if the battery voltage drops below 11.00 Vdc
- Automatic switching device for AES fridge / compressor fridge. While the vehicle is moving, the control unit powers the fridge from the starter battery. When the vehicle is parked, the fridge is powered by the service battery.
- 3-way connector for connecting the service battery and the starter battery
- Compact and lightweight design (H x W x D) 130 x 270 x 170.5 mm. Weight 1700 g



TP310A Touch Control Panel

CONTROLS:

- Service battery
- Clear water
- Waste water
- ON – OFF
- Mains connections
- Dimensions (W x H x D) 150 x 95 x 10 mm
- Construction: PCA wall-mounting bracket with screws and interlocking mechanism + toughened glass

CE - R10

TEB310ALF



Electronic control unit to control a camper with battery charger, connectors and fuses



The TEB310ALF is an analogue/digital electronic control unit fitted with a 230 V AC / 12 V DC battery charger which is designed to supply power to all the required 12 V DC electrical appliances in a motorhome.

The electronic control unit is fitted with a digital control module that performs the following functions:

- Charging of all connected batteries via the 230 V AC mains supply: service batteries (up to 20 A/h) and starter batteries (6 A max.)
- Distribution of current to connected 12 V loads
- Fuses to protect connected 12 V loads
- Monitoring of battery voltage and charge level (LITHIUM only) via the TP310ALF panel
- Recharging of the service battery as well as the starter battery whilst driving (via the alternator)
- Battery charging via an external solar panel.
- Disconnection of all loads from the battery, by operating the dedicated switch, during storage.
- Charging selector for 4 battery types: LITHIUM, AGM, ACID, GEL
- CI BUS connector, to be connected to LITHIUM batteries (latest generation) to display their charge level directly on the TP310A panel
- Automatic shut-off device for electrical loads if the battery voltage drops below 11.00 Vdc
- Automatic switching device for AES fridge / compressor fridge. Whilst the vehicle is in motion, the control unit powers the fridge from the starter battery. When the vehicle is stationary, the fridge is powered by the service battery.
- RJ10 connector for connecting the TEB310P touchscreen control panel using a simple 4-pin cable.
- Connectors for connecting fresh water and waste water tanks
- 4-way connector for connecting the service battery and starter battery
- Compact and lightweight design (H x W x D) 130 x 270 x 170.5 mm. Weight 1700 g



TP310ALF Touch Control Panel

CONTROLS:

- Engine battery and charging
- Interior and exterior lights
- Fresh water
- Waste water
- Water pump
- ON – OFF
- Mains connections
- Dimensions (W x H x D) 150 x 95 x 10 mm
- Construction: PCA wall-mounting bracket with screws and interlocking mechanism + toughened glass

CE – R10



TEB310D Digital

Electronic control unit to control a camper with battery charger, connectors and fuses



The TEB310D is an analogue/digital electronic control unit fitted with a 230 V AC / 12 V DC battery charger which is designed to supply power to all the required 12 V DC electrical appliances in a motorhome.

The electronic control unit is fitted with a digital control module that performs the following functions:

- Charging, via the 230 V AC mains supply, of all connected batteries: service batteries (up to 20 A/h) and starter batteries (6 A max.)
- Distribution of current to connected 12 V loads
- Fuses to protect connected 12 V loads
- Monitoring of battery voltage via the TP310D panel
- Recharging of the service battery as well as the starter battery whilst driving (via the alternator)
- Charging of batteries via an external solar panel.
- Disconnection of all loads from the battery, by operating the appropriate switch, during storage.
- Charge selector for 4 battery types: LITHIUM, AGM, ACID, GEL
- Connectors: 1x CI BUS, 2x CAN Bus for transmitting information to a compatible digital display, including those from other manufacturers (on request)
- Automatic load shut-off device if the battery voltage drops below 11.00 Vdc
- Automatic switching device for AES fridge / compressor fridge. Whilst the vehicle is in motion, the control unit powers the fridge from the starter battery. When the vehicle is stationary, the fridge is powered by the service battery.
- RJ10 connector for connecting the TEB310P touchscreen control panel using a simple 4-pin cable.
- Connectors for connecting fresh water and waste water tanks
- 3-way connector for connecting the service battery and starter battery
- Compact and lightweight design (H x W x D) 130 x 270 x 170.5 mm. Weight 1700 g



TP310D Touch Control Panel

CONTROLS:

- Service panel
- Fresh water
- Waste water
- ON - OFF
- Mains connections
- Dimensions (W x H x D) 150 x 95 x 10 mm
- Construction: PCA wall-mounting bracket with screws and interlocking mechanism + toughened glass

CE - R10



TBOOSTER PRO 1245



12V DC/DC converter 70 A

The TBooster PRO 1245 is a DC/DC converter designed for optimal charging of 12V service batteries while driving.

Thanks to step up/down technology, this device compensates the alternator voltage, making it appropriate to handle each stage of battery charging. In addition to being indispensable in EURO6 vehicles, where the energy-saving strategy makes the alternator voltage variable according to the driving status, this device is also particularly suitable for conventional alternators because it guarantees a full and more efficient charge, especially in systems with particularly long wiring.

- Step up/down converter to adapt alternator voltage
- Charging curve for lead acid, gel, AGM and lithium batteries
- Temperature compensation (if temperature sensor is connected)
- Starter battery voltage control
- Inhibits the discharge of the service battery to the starter battery
- Compact and lightweight design
- High efficiency, over 90%
- "Bridge" function (with manual selector) to charge the starter battery in case of emergency
- Possibility of limiting power in order not to overload the alternator

Technical specifications	
Input voltage range	10,5 – 15V
Max input voltage	16
Max input current	65A
Max charging current	70A
Rated current	45A
Service battery	Lead acid, Gel, AGM and Lithium batteries
Consumption with engine off	<1mA
Efficiency	>=93%
Safety	OUTPUT overcurrent (fuse+electronic), overvoltage Overtemperature (with derating)
Connections	Battery cable cross-section up to 16mm ²
Dimensions (L x D x H)	167 x 185 x 72
Weight	1140g

TBOOSTER PRO 1225




Compatible with CI-BUS systems

The TBooster PRO 1225 is a DC/DC converter designed for optimal charging of 12V service batteries while driving.

Thanks to step up/down technology, this device compensates the alternator voltage, making it appropriate to handle each stage of battery charging. In addition to being indispensable in EURO6 vehicles, where the energy-saving strategy makes the alternator voltage variable according to the driving status, this device is also particularly suitable for conventional alternators because it guarantees a full and more efficient charge, especially in systems with particularly long wiring.

- Step up/down converter to adapt alternator voltage
- Charging curve for lead acid, gel, AGM and lithium batteries
- Temperature compensation (if temperature sensor is connected)
- Starter battery voltage control
- Inhibits the discharge of the service battery to the starter battery
- Compact and lightweight design
- High efficiency, over 90%



Technical specifications	
Input voltage range	12V
Max input voltage	16V
Max input current	30A
Max charging current	32A
Rated current	25A
Service battery	Lead acid, Gel, AGM and Lithium batteries
Consumption with engine off	<1mA
Efficiency	>=90%
Safety	OUTPUT overcurrent (fuse+electronic), overvoltage Overtemperature (with derating)
Connections	Battery cable cross-section up to 16mm ²
Dimensions (L x D x H)	95 x 148 x 55
Weight	360g

ACCESSORIES FOR BATTERIES AND TBOOSTERS



TCP Optional control panel

Connected to the battery with a standard patch cable



Monitor battery parameters:
State of charge (SOC%)
Voltage
Current
Power




Monitor battery status and alarms



Slide switch to turn ON / OFF the battery

RJ10 CONNECTOR CI-BUS LOW-PROFILE



Push-button to activate storage mode



Custom Low-profile RJ45 connector to fit under the seat of a Stellantis chassis.

Safe-lock system thanks to the additional frame fixed on the battery

Available in different setup to connect different devices:

- **CTB1** – 4m long **CI-Bus** connection for Teleco **TEB** or other CI-Bus appliances
- **CTBP1** - 4m long **CI-Bus** connection for Teleco **TEB** or other CI-Bus appliances + 3m long cable with remote pushbutton to control **1 battery**
- **CTBP2** - 4m long **CI-Bus** connection for Teleco **TEB** or other CI-Bus appliances + 3m long cable with remote pushbutton to control **2 batteries**

Connection cables from the battery to TEB310 electrical units

CTB1 - 1 Battery - 1 TEB310


- RJ45 connector low profile
- CI-BUS connection to TEB



CI-BUS connector from the battery to TEB310 without the extension of the ON-OFF button


CTBP1 - 1 Battery - 1 TEB310 with push button

- RJ45 connector low profile
- CI-BUS connection to TEB
- Remote ON/OFF Button to control the battery




CTBP2 - 2 Batteries - 1 TEB310 with push button

- RJ45 connector low profile
- CI-BUS connection to TEB
- Remote ON/OFF Button to control 2 batteries



Battery kits and connection cables > TBOOSTER 1245



SINUS INVERTER

INVERTER with pure sine wave

Pure sine wave inverters are ideal for powering all on-board household devices at 230 Volts at up to 2000 Watts continuous power and 4000 Watts peak power.

They operate with the 12V current supplied by the battery and, thanks to the ACT (AC Transfer) function, also with an external mains current if available when the vehicle is stationary. The external mains source has priority and switching is performed automatically in order to conserve battery power.

Advanced control electronics optimise operation and ensure protection against short circuits and overloads.

Schuko output sockets and a USB port for charging mobile devices are available.

TI 2000 SI-ACT - TI 1500 SI-ACT

TI 600 SI-ACT - TI 400 SI-ACT

Tips on proper operation:

- Use an alternator with a capacity of at least 90A to run a Telair Silent 5400H air conditioner when driving
- Service battery capacity must be at least 100 Ah



TI 2000 SI-ACT	
Rated input voltage (AC)	230 V / 50 Hz
Rated input voltage (DC)	12 V
Input operating range (DC)	10,5 - 15,5 V
Output wave form	Pure sine wave
Rated output voltage	230 V / 50 Hz
Continuous output power	2000 W
Peak output power	4000 W
Short circuit / overload protection	Yes
Dimensions (LxDxH)	380x220x90 mm
Weight	5600 g

TI 1500 SI-ACT	
Rated input voltage (AC)	230 V / 50 Hz
Rated input voltage (DC)	12 V
Input operating range (DC)	10,5 - 15,5 V
Output wave form	Pure sine wave
Rated output voltage	230 V / 50 Hz
Continuous output power	1500 W
Peak output power	3000 W
Short circuit / overload protection	Yes
Dimensions (LxDxH)	320x220x90 mm
Weight	5300 g



TI 600 SI-ACT	12V	24V
Rated input voltage (DC)	12 V	24 V
Input operating range (DC)	11 - 14,5 V	22 - 29 V
Output wave form	Pure sine wave	Pure sine wave
Rated Output Voltage	230 V / 50 Hz	50 Hz
Continuous output power	600 W	600 W
Peak output power	1200 W	1200 W
Short circuit / overload protection	Yes	Yes
Dimensions (LxDxH)	300x143x75 mm	300x143x75 mm
Weight	1900 g	1900 g

TI 400 SI-ACT	
Rated input voltage (DC)	12 V
Input operating range (DC)	11 - 14,5 V
Output wave form	Pure sine wave
Rated Output Voltage	230 V / 50 Hz
Continuous output power	400 W
Peak output power	800 W
Short circuit / overload protection	Yes
Dimensions (LxDxH)	210x105x60 mm
Weight	1000 g

BATTERY CHARGER TBC3i PRO

30/20/250



TBC PRO battery chargers are high performance devices that run on AC mains power supplies (universal range 100 - 240 V AC, 50 - 60 Hz); they have been designed and manufactured to charge TELECO lithium batteries. They have been designed with special functions to charge LiFePO4 cells. Moreover, they are compatible for use with lead-acid batteries.

Their 500 W power rating shortens charge times considerably.

The battery chargers have a display showing key parameters such as instantaneous voltage, instantaneous current, percentage charge and residual capacity.

Two models are available, one for 12 V batteries and one for 24 V batteries.

These battery chargers are compatible with all car park charging units.

Model	TBC PRO 1230	TBC PRO 2417
Rated voltage	14.6 V +/- 0.1 V	29.2 V +/- 0.1 V
Rated current	30 A	17 A
Pre-charge 1 (@2.5 V/Cell)	7.5 A	4.25 A
Pre-charge 2 (@2.9 V/Cell)	15 A	8.5 A
Charge 3 (<30% Rated Current)	8 A	5 A
Power	500 W	
Efficiency	>85 % full charge	
Rated input voltage	100 - 240 V	
Frequency	47 - 63 Hz	
Polarity inversion	Protection with automatic shutdown	
Short Circuit	Protection with automatic shutdown	
Overload	Protection with current limit	
Dimensions (LxDxH)	152x275x70 mm	
Weight	2400 g	

Supplied: 230 V AC mains cable, red/black cables with crocodile clips for attachment to battery

Innovative TBC3i battery chargers offer outstanding construction quality and have a particularly light, compact design that helps save valuable space inside the camper.

Wiring and connections have been minimised to make installation fast and simple.

TBC3i battery chargers consist of a combination of latest-generation units; these include a mains battery charger, a charge converter from the alternator and a charge regulator with MPPT technology for solar panels, ensuring there is always an energy source in the camper.

Batteries are always charged automatically, both during the standby or when driving.

Depending on the model, the integrated charge converter always ensures a complete recharge during both short and, of course, long trips.

All of them have an integrated system to maintain battery charge even during long periods of storage and have eight different charge curves for lead-acid, AGM, GEL and LiFePO4 batteries.

Their LCD displays have been specially developed for these units and show all the key information.

These battery chargers are compatible with all car park charging units.

TBC3i PRO 30/20/250

Operation from mains AC

Rated voltage (AC)	110 V - 230 V / 45 - 65 Hz
Operating range (AC)	90 V - 270 V (max. 305 V, for 5 sec)
Max. absorbed current (AC)	360 W
Service / Start battery charge current	20 A / 4 A
AC Power Limit function	Yes

Charge Converter 12 V/12 V Voltage Max Service

Battery Charger current	30 A
Automatic D+ activation	Yes
Start battery/Alternator Voltage (Euro 6) / Max. current.	10.5 - 16.5 V / 42 A
Max. current II limit (settable)	25 A

MPPT Solar Regulator

Solar Module Power (Pmax)	50 - 250 Wp
Solar Module max. current	15 A
Solar Module max. voltage	36 V
Start / Service max. battery charger current	18.0 / 4.0 A
AES cooling terminal	Yes

Starter Battery

Rated Voltage / Min. recommended capacity	12 V / >60 Ah
---	---------------

Service Battery, IU10U20U3

Lead-acid / LiFePO4 voltage	12 V / 12.0 - 13.3 V
Battery capacity (settable)	45 - 280 Ah

Specifications

N. of charge programmes for Lead-Acid / Gel / AGM battery	4
N. of charge programmes for LiFePO4 battery	4
Start / Service battery voltage sensors	Yes
Temperature compensation (Lead-Acid) / Protection (LiFePO4)	Yes
Automatic regeneration (Lead-Acid / Auto Wake Up (LiFePO4)	Yes
Battery Trainer (Pulser) for Lead-Acid Service Battery, can be activated	Yes
LiFePO4 control input – BMS for charge stop	Yes
Assembly position	All
Operating Temperature	-20 to +45 °C
Variable-speed fan, temperature-controlled	Yes
Gradual charge reduction for Overheating	Yes
Safety Disconnect in the event of Overheating	Yes
Waterproof rating	IP 21
Environmental conditions	Max 95% RH, No Condensation
Dimensions (LxDxH) - incl. assembly flange, without connections	217 x 250 x 85 mm
Weight	2700 g

Supplied: 230 V AC mains cable, 825 temperature sensor, Manual

BLACK COOLFLEX SOLAR PANELS - FLEXIBLE

Mono-Crystalline High Dissipation

- 50% lighter than traditional rigid panels
- Special surface finish to maximise the transmittance of sunlight
- 10 degrees maximum curvature
- Double ETFE coating for improved weather resistance.
- **9-layer composition, with a layer of flame-resistant PCB for greater sturdiness and better heat dissipation**

TBCF 100WS




10% maximum curvature



9-LAYER COMPOSITION

ETFE
Protection Layer
EVA
Solar Cell
EVA
Protection Layer
PCB
EVA
ETFE



Black COOLFLEX Solar Panels mono-crystalline

Specifications	TBCF 100WS	TBCF 135WS	TBCF 150WS	TBCF 200WS
Rated power (P _{max}):	100 W	135 W	150 W	200 W
Rated voltage P _{max} (V _{mp}):	19.8 V	19.8 V	19.8 V	18.5 V
Rated current P _{max} (I _{mp}):	5.05 A	6.82 A	7.58 A	10.76 A
Open circuit voltage (V _{oc}):	23.3 V	23.3 V	23.3 V	21.7 V
Closed circuit current (I _{sc}):	5.45 A	7.36 A	8.19 A	11.29 A
Module efficiency (η _m):	22.42 %	22.42 %	22.62 %	22.68 %
Working temperature:	-20°C ~ + 75°C	-20°C ~ + 75°C	-20°C ~ + 75°C	-20°C ~ + 75°C
Lead (length/cross-section):	3 m /2.5 mm ²	3 m /2.5 mm ²	3 m /2.5 mm ²	3 m /2.5 mm ²
Module size (LxWxH) (without feet):	1080x510x4 mm	1090x680x4 mm	1130x710x4 mm	1400x780x4 mm
Weight (without feet):	3.75 Kg	4.7 Kg	4.7 kg	6.5 kg



BLACK FLEXIBLE SOLAR PANELS Mono-Crystalline

TBSF 110WS



70% maximum curvature

Monocrystalline Flexible Solar Panels

Specifications	TBSF 110WS
Rated power (P _{max}):	110 W
Rated voltage P _{max} (V _{mp}):	18.8 V
Rated current P _{max} (I _{mp}):	5.86 A
Open circuit voltage (V _{oc}):	22.3 V
Closed circuit current (I _{sc}):	6.21 A
Module efficiency (η _m):	18.2 %
Working temperature:	- 20°C ~ + 65 °C
Lead (length/cross-section):	900 mm / 2.5 mm ²
Module size (LxWxH) (without feet):	900 mm / 2.5 mm ²
Weight (without feet):	2.1 Kg

- STC: irradiance 1000W/m², cell temperature 25°C, air mass AM1.5 according to EN60904-3
 - Average efficiency reduction of 4.5% at 200W/m² according to EN60904-1



ACCESSORIES



K2PS
 Connection kit with diodes for 2 solar panels
 2 Adapters with 10A diodes
 2 double couplers for positive and negative
 CPP Connectors for extension cables



6 m extension cable

SPCA/TSP
Aluminium cable guideRigid solar panel attachment kit:
4 ABS feet + spoiler for quick panel attachment
with self-tapping screwsTSP64 - Black
Narrow plastic cable guide. Black
colourTSP64
Narrow plastic cable guideCleaning and glueing kit
(DEKASYL MS-5)
feet for rigid solar panel

SOLAR PANELS 450W


Mono-Crystalline - TOPCon

TBS 450WS



N.B. The 450W panel can only be used with MPPT controllers with a minimum rating of 40A. It can charge the battery at a rate of up to over 25A.

TOPCON Cell



Specifications	TBS 450WS
Rated power (Pmax):	450 W
Rated voltage Pmax (Vmp):	33.22 V
Rated current Pmax (Imp):	13.55 A
Open circuit voltage (Voc):	39.78 V
Closed circuit current (Isc):	14.38 A
Module efficiency (η_m):	22.52 %
Working temperature:	- 40°C ~ + 85 °C
Lead (length/cross-section):	1200 mm / 4 mm ²
Module size (LxWxH) (without feet):	176,2 x 113,4 x 3 cm
Weight (without feet):	24 Kg

- STC: irradiance 1000W/m², cell temperature 25°C, air mass AM1.5 according to EN60904-3
 - Average efficiency reduction of 4.5% at 200W/m² according to EN60904-1



Attachment kit:



Rigid solar panel attachment kit:
 4 ABS feet + spoiler for quick panel attachment with self-tapping screws

BLACK SOLAR PANELS


Mono-Crystalline




TBS 110WS
Rigid



TSP 130WS Rigid
TSP 145WS Rigid



Conventional monocrystalline cel



PERC Cell

Black Mono-Crystalline Solar Panels

Specifications	TBS 110WS	TBS 185WS	TSP 145WS	TSP 130WS
Rated power (Pmax):	110 W	185 W	145 W	130 W
Rated voltage Pmax (Vmp):	19.45 V	20.9 V	21.55 V	19.4 V
Rated current Pmax (Imp):	5.66 A	8.85 A	8.39 A	6.71 A
Open circuit voltage (Voc):	23.1 V	24.7 V	18.15 V	23.4 V
Closed circuit current (Isc):	5.95 A	9.38 A	7.99 A	7.12 A
Module efficiency (η_m):	20.54 %	20.68 %	20,79%	16 %
Working temperature:	-40°C ~ + 85°C	-40°C ~ + 80°C	-40°C ~ + 85°C	-40°C ~ + 85°C
Cable (length/cross-section):	900 mm/2.5 mm ²	900 mm/2.5 mm ²	900 mm/2.5 mm ²	650 mm/4 mm ²
Module size (LxWxH) (without feet):	1160x450x30 mm	1230x705x30 mm	1050x670x35 mm	1065x670x35 mm
Weight (without feet):	5.7 kg	10.0 kg	7.7 kg	7.8 kg
PERC Cell		•		
TOPCON Cell	•		•	

- STC: irradiance 1000W/m², cell temperature 25°C, air mass AM1.5 according to EN60904-3
 - Average efficiency reduction of 4.5% at 200W/m² according to EN60904-1



BLACK PORTABLE SOLAR PANELS

Mono-Crystalline



Specifications	TBSP 90WS
Solar Panel	90W (3pcs) Monocrystalline silicon
USB Output	5V / 2.4A
USB 3.0QC Output	5V/2.4A, 9V/2A, 12V/1.5A
DC Output	12V-18V / 5A
Type C Output	5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/2A, PD 60W
Folded size	545x350x30mm
Unfolded size	1058x545x5mm



DC+ USB+ QC 3.0 + Type C interface

PORTABLE POWER STATION



Teleco portable batteries to power equipment anywhere. Light, with user-friendly carry handle. Easy to charge via mains, cigar lighter socket or solar panel. Loads can be powered via sinusoidal output, 12 V output or USB ports.

PPS1000	
Battery capacity	1110Wh
Battery type	Li-ion
Input for charging from AC mains	100÷240V 50/60Hz
Solar panel input	18÷30V / 3A
Cigar lighter charging input	✓
AC output	220÷240V 50/60Hz
AC output rated power	1000W (2000W peak)
USB output	5V / 2,1A
QC 3.0 output	5V/3A - 9V/2A - 12V/1,5A
Type C USC output	PD 60W - 5V/3A - 9V/3A - 12V/3A 15V/3A - 20V/3A
DC output	12V / 8A
Sine output wave form	✓
Response time	≤5ms
Net weight	11kg
Size LxDxH	320x230x260 mm
Operating temperature	-10 ÷ +60°C
Overload protection	✓
Short circuit protection	✓
Overheating protection	✓
Overcharging protection	✓
Excessive discharge protection	✓

PPS500	
Battery capacity	460Wh
Battery type	Li-ion
Input for charging from AC mains	100÷240V 50/60Hz
Solar panel input	12÷18V / 3A
Cigar lighter charging input	✓
AC output	220÷240V 50/60Hz
AC output rated power	500W
USB output	5V / 2,1A
Type C USC output	5V / 3A
DC output	10÷14,6V / 8A
Sine output wave form	✓
Response time	≤5ms
Net weight	6,5kg
Size LxDxH	290 x 159 x 158mm
Operating temperature	-20 ÷ +60°C
Overload protection	✓
Short circuit protection	✓
Overheating protection	✓
Overcharging protection	✓
Excessive discharge protection	✓

MPPT SPC 15/1B - MPPT SPC 40/1B



Technical data		MPPT SPC15/1B	MPPT SPC40/1B
Battery parameters	System Voltage	12V	12V
	Rated Charging Current	15A	40A
	Battery Type Available	Lithium, Gel, AGM, Liquid	Lithium, Gel, AGM, Liquid
	Temperature compensation	YES	YES
	Overcharge Protect	15,5V	15,5V
Gel, AGM, Liquid charging parameters	Boost Voltage	Programmable 14÷14,8V, Default 14,5V	Programmable 14÷14,8V, Default 14,5V
	Equalization Voltage	Programmable 14÷15V, Default 14,8V	Programmable 14÷15V, Default 14,8V
	Float Voltage	Programmable 13÷14,5V, Default 13,7V	Programmable 13÷14,5V, Default 13,7V
Lithium charging parameters	Low Voltage Disconnect	10,8÷11,8V, Default 11,2V	10,8÷11,8V, Default 11,2V
	Charging Target Voltage	Programmable 10÷17V, Default 14,4V	Programmable 10÷17V, Default 14,4V
	Low Voltage disconnect	Programmable 9÷15V, Default 10,6V	Programmable 9÷15V, Default 10,6V
Panel parameters	Max Voltage on PV terminals	55V	100V
	Max Input Power	200W	520W
	Day/Night Threshold	8V	8V
System parameters	Max Tracking Efficiency	>99,9%	>99,9%
	Max Charge conversion	98%	98%
	Self-Consumption	0,2W	0,2W
	Wireless communication	YES	YES
	Operating Temperature	-20 ÷ +55°C	-20 ÷ +55°C
	Installation	Wall Mount	Wall Mount
	Size LxDxH	143 x 107 x 28mm	182 x 133 x 40mm
	Net Weight	543g	1330g
	Protection Degree	IP54	IP54

TELECO app with notification of low battery alarm, compatible with MPPT SPC 15/1B and SPC 40/1B

Solar Charge Controller MPPT - wireless

The solar charge controller is based on advanced Maximum Power Point Tracking (MPPT) technology which allows a conversion efficiency of up to 98%.

The solar charge controller has the following key characteristics:

- Use of innovative MPPT technology to maximise tracking efficiency (>99.9%)
- Use of fully digital technology with high charge conversion efficiency (up to 98%)
- The LCD design ensures easy-to-read operating data and working conditions (only for MPPT SPC15/1, MPPT SPC 20/1B e MPPT SPC30/1B versions)
- Real-time energy statistics function
- Flexible system battery selection: liquid, gel, AGM and lithium
- 4-stage battery charging process: MPPT, boost, equalization, float
- Dual automatic protection to avoid exceeding the rated charging power and current
- Multiple load control modes: Always on, Streetlight, User-defined mode
- Two USB interfaces (available on the SCP15/1 model) to charge devices
- Wireless communication available on the MPPT SPC 20/1B, MPPT SPC 30/1B, MPPT SPC15/1B and MPPT SPC40/1B models
- The installed remote temperature sensor helps extend battery life.



MPPT SPC 15/1 - MPPT SPC 20/1B MPPT SPC 30/1B



TELECO app with notification of low battery alarm, compatible with MPPT 20 1/B and 30/1B

Technical data	MPPT SPC15/1	MPPT SPC20/1B	MPPT SPC30/1B
System voltage	12 V	Automatic recognition 12 V / 24 V	
Maximum charge current	15 A	20 A	30 A
Boost voltage	14,5 V @ 25 °C	14,0~14,8 V / 28,0~29,6 V @ 25 °C (Default setting: 11.2 V: 14,5 / 29 V)	
Equalization voltage	14,8 V @ 25 °C (Liquid, AGM)	14,0~15,0 V / 28,0~30,0 V @ 25 °C (Default setting: 11.2 V: 14,8 / 29,6 V)	
Float voltage	13,7 V @ 25 °C	13,0~14,5 V / 26,0~29,0 V @ 25 °C (Default setting: 11.2 V: 13,7 / 27,4 V)	
Disconnection voltage	10,8~11,8 V, SOC1~5 (Default setting: 11,2 V)	10,8~11,8 V / 21,6~23,6 V, SOC1~5 (Default setting: 11.2 V: 11,2 / 22,4 V)	
Disconnection voltage	-4,17 mV/K per cell (boost, equalization) -3,33 mV/K per cell (float charge)		
Battery type	Gel, AGM, Liquid, Lithium (Default setting: Gel)		
Maximum voltage on photovoltaic terminal	35 V (*1)	75 V a -40 °C (*1) / 70 V a 25 °C (*1)	
Maximum input power	200 W	260/520 W	390/780 W
Output current	10 A	20 A	30 A
USB interface	5 V - 2 A	x	x
Wireless	x	v	v
Operating mode	Always on / Streetlight / User-defined mode		
Maximum tracking efficiency	>99.9 %		
Maximum tracking efficiency	97,5%	98%	
Dimensions	189x96x53 mm	189x182x58 mm	189x182x64 mm
Weight	420 g	1 Kg	1,3 Kg
Self-consumption	0,2 W	≤8 mA (12 V), ≤12 mA (24 V)	
Power terminals	8AWG (10 mm²)	6AWG (16 mm²)	
Ambient temperature	-20 °C / +55 °C		

SPC20/1 SPC10/1

Solar Charge Controller PWM



SPC20/1



SPC10/1

SPC20/1

- Large LED screen, adjustable charge/discharge parameters with memory function.
- Full 3-point PWM charge control.
- All installed protection devices are of the automatic reset type: built-in overcurrent protection, short-circuit protection, open-circuit protection, reverse connection protection.
- Dual USB output. Maximum output current 1.5 A

SPC10/1

- Full 3-point PWM charging management
- All installed protection devices are of the self-resetting type: built-in overcurrent protection, short-circuit protection, open-circuit protection, reverse connection protection.

TECHNICAL DATA	SPC 20/1	SPC 10/1
System voltage	12 V / 24 V (Automatic recognition)	12 V
Rated charge current	20 A	10
Rated discharge current	10 A	10
Maximal solar voltage	max solar voltage 23 V	25 V
Battery type	BAT1= lead acid battery 12 V LIT1= ternary lithium battery (3 S / 11.1 V) LIT2= lithium-iron-phosphate battery (4 S / 12.8 V)	---
End-of-charge voltage	Lead acid battery: 14.4 V (non-adjustable) Ternary lithium battery: 12.6 V (non-adjustable) Lithium-iron-phosphate battery: 14.2 V (non-adjustable)	---
LVD	Lead acid battery: 12.6 V (adjustable: 11.5 V ~ 13 V) Ternary lithium battery: 10.5 V (adjustable 10 V ~ 11 V) Lithium-iron-phosphate battery: 12 V (adjustable 11.5 V ~ 12.5 V)	---
LVR	Lead acid battery: 10.7 V (adjustable: 9.5 V ~ 11.5 V) Ternary lithium battery: 9 V (adjustable 8.5 V ~ 9.5 V) Lithium-iron-phosphate battery: 10 V (adjustable 9.5 V ~ 10.5 V)	---
Float Voltage	Lead acid battery: 13.7 V (adjustable: 13 V ~ 15 V) Ternary lithium battery: 12 V (adjustable 11.5 V ~ 12.5 V) Lithium-iron-phosphate battery: 13.8 V (adjustable 13 V ~ 14.5 V)	---
Charge activation voltage	8 V (from solar panel)	13,3 ±0,3V
USB output	2 USB; 5V/2A (MAX)	---
Standby current	<10 mA	<5mA
Operating Temperature	-35 °C / +60 °C	-10 °C / +55°C
Dimensions/Weight	133 x 70 x 35 mm / 140 g	133 x 70 x 35 mm / 140 g
*The voltages shown in the table indicate the thresholds for 12 V applications. With 24 V applications, double the indicated values.		

CONNECTIVITY

Stay connected with the new Teleco systems – COMBISAT WiFi and FLATSAT WiFi.

A single Universal antenna with an integrated mini 5G-4G antenna to receive **Satellite, Mobile and WiFi signals**

You will always have access to your favourite programmes on your Smart TV.

When 5G, 4G or 3G signals are not available in the area where you are coming, fear not: just activate your satellite dish and, within moments, you will be watching dozens of channels on your Smart TV.

And if there is a Wi-Fi hotspot nearby, you can simply connect your router to act as a booster.

A fast and simple solution that lets you choose what works best for you in a matter of seconds.



ANTENNAS FOR 4G-5G ROUTERS

TAW85 M2



MINI OUTDOOR ANTENNA FOR WLT58 and WLT24EX2 routers

- MIM02 model with dual antennas
- Frequency: 700–6000 MHz
- 2 cables, each 5 metres long

TAW85 M1



SMALL OUTDOOR ANTENNA FOR ROUTER WLT24 EX2

- MIM01 model with 1 antenna
- Frequency: 700–6000 MHz
- 1 cable, 5 metres long

WING LAN1 1

OUTDOOR ROUTER ANTENNA

COMBINED WITH A DVB-T2 TERRESTRIAL ANTENNA

- Mobile frequency: 700–6000 MHz
- DVB-T2 frequency 170–590 MHz with amplifier

Internet Antenna 2G-3G-4G-5G +Omnidirectional TV Antenna + Radio




The **Wing-Lan 11** integrates an omnidirectional TV antenna for **DVB-T/T2 digital terrestrial** and **DAB+** radio signals with a high-efficiency internet antenna for 2G-3G-4G-5G signals. When paired with the TELECO router, it sets up a **WLAN WIFI** hotspot for browsing the internet, streaming and watching your favourite programmes.



ROUTER 5G WLT58

Wi-Fi 7



Portable 12Volt Wi-Fi Router 2 SIM Cards - Wi-Fi7

The WLT58 is a portable 5G router operating at 12 Vdc, capable of transforming any 2G/3G/4G/5G mobile phone signal into Wi-Fi via data SIM card (not supplied). Thanks to the two SIM card slots, you get to choose the mobile operator that provides the best signal in your location. It is compatible with all 4 mobile phone bands (5G LTE/4GLTE/3G/GSM).

The package includes two additional TS-9 antenna inlets and TS-9/SMA-F conversion cables to connect an external MIMO2 antenna TAW85 M2 (not supplied).



Optional:
wall mounting bracket

RECOMMENDED OUTDOOR ANTENNAS:

- TAW85 M2 (white or black)
- WING LAN11
- COMBISAT - FLAT SAT WiFi

Specifications

Standard	Compatible with Sub 6GHz, 802.11 a/b/g/n/ac/ax/be
Frequencies	[5G NR]: n1/n3/n5/n7/n8/n20/n28/n38/n40/n41/n71/n75/n76/n77/n78/n79 [LTE]: B1/B3/B5/B7/B8/B20/B28/B32/B38/B40/B41/B42/B43/B71 [UMTS]: B1/B5/B8
WiFi-7	2.4GHz-5GHz, WiFi 2*2 MIMO, 802.11 a/b/g/n/ac/ax/be DBDC BE 5000, compatible Easy mesh R4
5G SA NSA Mode	5G NR: (DL/UL) 4Gbps / 900Mbps
Max data transmission speed	LTE: (DL/UL) 2.0Gbps / 200Mbps
Diversity function	Supported
MIMO	DL 4x4 MIMO
Chipset	Qualcomm SDx72-0
Memory	Modem: 16Gb EMMC+8Gb LPDDR4
Power consumption	< 24W
Power supply	DC 12V/2A
USOM/SIM	Supports SIM/USIM/UIM, standard 6 PIN SIM card, 3V/1.8V SIM card, internal push-pull SIM slot
LED	Indication of 12V presence; Indication of WIFI; Indication of 5G, 4G
USB	USB 2.0
Antennas	6 LTE/NR, N41/77/78/79 8dBi high gain antennas, 2*TS-9 antenna connectors
Buttons	Power supply, Reset, WPS
Ethernet port	1*WAN + 1*LAN, 1*1.0 Gbps
Voice	1*RJ11, support VoIP/VoLTE/VoNR
Reset	Pinhole
NFC	Supports WIFI connection with NFC
ESD	ESD circuit protection, Contact }8KV, air }10KV
Temperature for Operation	0 °C ~ +45 °C
Temperature for storage	-20 °C ~ +70 °C
Humidity	5% ~ 95%
Dimensions	100x100x180 mm

WLT24EX2 WI-FI ROUTER 4G



Portable 12Vol
WiFi router 4G

**with WiFi signal repeater
2 SIM Cards**

The WLT24EX2 is a portable 12Vdc router that can turn any mobile signal into WiFi via a data SIM card (not included). It is compatible with all mobile signal bands (LTE/4G/3G), and can act as a **WiFi signal repeater** by distributing any WiFi signal from nearby sources into the motorhome.

TECHNICAL FEATURES WLT24EX2

- LTE/4G/3G reception frequencies
800(B20), 900(B8), 1800(B3), 2100(B1), 2600(B7).
- 2 internal 3G-4G-LTE-Wifi antennas
- WiFi signal repeater
- 2 SMA plugs for connecting an external antenna on the roof of the vehicle
- 2 SIM card readers
- 1 Ethernet port
- LTE category 4
- LTE DL 150Mbps/UL 50Mbps
- DC power supply: 10.5/14.5V/1A
- Dimensions: 151 x 150 x 48 mm

RECOMMENDED OUTDOOR ANTENNAS:




- TAW85 M1 (white or black)
- WING LAN11
- COMBISAT - FLAT SAT WiFi




TRB4
Optional:
wall mounting bracket

AUTOMATIC SATELLITE ANTENNAS



		Combisat WiFi	Flatsat WiFi	Flatsat Classic BT	Telesat BT
HD		✓	✓	✓	✓
DVBS-2		✓	✓	✓	✓
Mini Panel					
Number of satellites		Display	Display	Display	Display
SMART control		16	16	16	16
LNB protective cover		option	option	option	option
SKEW		—	—	—	—
Overall dimensions		—	—	—	—
Closed				  	 
Weight (approx.)		—	—	8,8Kg	—
		9,0Kg	9,0Kg	9,0Kg	9,0Kg
		—	—	10,8Kg	10,6Kg
Dish dimensions		—	—	49x45,5cm	—
		63,5x59cm	63,5x59cm	63,5x59cm	63,5x59cm
		—	—	85x78cm	85x78cm
Optional		TWIN - BLACK COLOUR	TWIN	TWIN - BLACK COLOUR	TWIN - BLACK COLOUR

FOOTPRINT



Footprint: advice on choosing a satellite dish

Reception of television and radio signals is guaranteed within the coloured areas (footprints). Cloud cover and rain could negatively affect reception of the satellite signal. So it is important, when choosing your satellite system, to check carefully that the dimensions of the dish are sufficient to receive a good satellite signal in the places that you will be visiting.



Footprint Legend



Satellite Antennas with automatic alignment



Teleco stands out against other brands through the use of lightweight but very durable materials. This allows us to guarantee that the equipment will not deteriorate over their long working life.

The weight and height of Teleco automatic antennas are reduced to a minimum without compromising quality.

- Anti-torsion arm with aerodynamic profile.
- Aluminium casting in special DIE-CASTING injection technology (lighter and stiffer) with anti-corrosion epoxy coating.
- Steel and bronze gears.
- Motorised system with steel and bronze gears for perfect and stable pointing of the satellite.
- Built-in safety system: automatic lowering of the antenna upon vehicle startup.

Flatsat Easy BT	Flatsat Easy Skew BT SMART
✓	✓
✓	✓
	
16	16
option	✓
✓	✓
—	✓
 85 cm 17 cm	 85 cm 17.5 cm
 104 cm 17 cm	 104 cm 19.5 cm
10,5Kg	10,8Kg
11,6Kg	12,0Kg
—	
72x67cm	72x67cm
91x85cm	91x85cm
TWIN - QUAD (mod. 70 only)	TWIN



CONTROL BOX

The new super-compact control box with 16 stored satellites is used to autonomously control all the New Flat Sat and Telesat Automatic Satellite Antennas. It features an easy-to-use OLED display and can be controlled from a smartphone via Bluetooth. All software updates - when made available on the TELECO App - can be made automatically by the end user on their smartphone via Bluetooth.

The antenna can be controlled in 5 different ways:

- 1) By pressing a key on the control unit
- 2) By Smartphone through the TELECO App (Free) via Bluetooth
- 3) With the New Mini Panel with Display
- 4) Via the CI Bus control panel (not included)
- 5) If the antenna is connected to a Teleco TV of the TEK series, it can be controlled directly through the remote control (Komfort and Elegance models)



App TELECO



The Teleco App is available for free in both iOS and Android. Selecting the Automatic Antenna icon takes you to the dedicated menu showing all the information that will make using the antenna extremely simple:

Compass indicating the direction from which the selected satellite signal is coming (Immediately ensures you do not park in front of an obstacle)

LNB skew value to optimise the incoming signal at the user's parking position;

List of 16 satellites saved in the Memory.

Firmware update When an update becomes available the user will receive it directly on the App and can install it on the antenna easily and automatically via Bluetooth from his/her smartphone

COMBISAT WIFI (NEW)

Always connected

Combined Satellite and WiFi antenna

A technologically advanced solution that lets you receive both satellite signals and NR5G, 4G, LTE and 3G mobile phone signals and thus watch your favourite programmes on both a TV and a Tablet.

**TWO
ANTENNAS
IN ONE**

FULL HD

Combisat WiFi consists of:

- 1 External satellite antenna
- 1 External mobile phone antenna
- 1 DVB-S2 Control unit complete with leads

TAW85

Antenna for NR5G, 4G, LTE, 3G mobile phone and Wi-Fi signals.

Compact and high-tech.

Can easily be installed on a camper/van roof. Equipped with a watertight cable gland so that satellite antenna cables can be inserted inside the vehicle. This antenna is equipped with a 5 m cable with connector. It is designed for quick connection to the WLT24EX2 Router (purchasable separately) which, via a SIM Card, generates a Wi-Fi source for SMART televisions, tablets, phones and computers.

HD Automatic Satellite Antenna. Equipped with a DVB-S2 control unit with 16 saved satellites. Has an OLED display and two buttons, one to start a satellite search with ease, the other to lower the dish. Can also be controlled with a smartphone via Bluetooth using the TELECO App. The control unit also has a CI Bus port. When made available on the TELECO App, all the software updates can be uploaded directly by the user with a smartphone via Bluetooth. The COMBISAT is compatible with all TVs equipped with the DVB-S2 tuner and with all satellite receivers. Safety system with automatic antenna closure when vehicle is started.

Optional:

SMART

- SMART function When the user changes channel with the TV remote control the antenna automatically points itself at the satellite broadcasting the selected channel.



DVB-S2 HD Control Unit

Power supply 12/24 V DC (10-31 V DC)

Max. Consumption: 3.2 A

Dimensions: 160x115x25 mm Weight: 250 g



Compatible with CI-BUS systems




Combisat WiFi 65

TWIN - OPTION: for 2 receivers

Weight: approx. 9.0 kg

Dish dimensions: 63.5 x 59 cm



- 1) The compact, watertight housing contains a WLAN Internet antenna and a cable guide with 2 or 3 holes for the satellite antenna cables.
- 2) Mobile Internet antenna: TAW85 reception frequency: 700-6000 MHz
For 5G-4G-3G-WLAN signals
Gain: 6 dBi Max
- 3) 5 mm cable cross section, 5 m cable length with SMA connector for connection to the WLT24EX2 router
- 4) Dimensions: 121x63x84 mm

FLATSAT WIFI



Always connected

Combined Satellite and WiFi antenna

A technologically advanced solution that lets you receive both satellite signals and NR5G, 4G, LTE and 3G mobile phone signals and thus watch your favourite programmes on both a TV and a Tablet.

**TWO ANTENNAS
IN ONE**

FULL HD

FlatSat WiFi consists of:

- 1 External satellite antenna
- 1 External mobile phone antenna
- 1 DVB-S2 Control unit complete with leads

TAW85

Antenna for NR5G, 4G, LTE, 3G mobile phone and Wi-Fi signals.

Compact and high-tech. Can easily be installed on a camper/van roof. Equipped with a watertight cable gland so that satellite antenna cables can be inserted inside the vehicle. This antenna is equipped with a 5 m cable with connector. It is designed for quick connection to the WLT24EX2 Router (purchasable separately) which, via a SIM Card, generates a Wi-Fi source for SMART televisions, tablets, phones and computers.

HD Automatic Satellite Antenna. Equipped with a DVB-S2 control unit with 16 saved satellites. Has an OLED display and two buttons, one to start a satellite search with ease, the other to lower the dish. Can also be controlled with a smartphone via Bluetooth using the TELECO App. The control unit also has a CI Bus port. When made available on the TELECO App, all the software updates can be uploaded directly by the user with a smartphone via Bluetooth. The FLATSAT WiFi is compatible with all TVs equipped with the DVB-S2 tuner and with all satellite receivers. Safety system with automatic antenna closure when vehicle is started.

Optional:

SMART

- SMART function When the user changes channel with the TV remote control the antenna automatically points itself at the satellite broadcasting the selected channel.



DVB-S2 HD Control Unit


Power supply 12/24 V DC (10-31 V DC)

Max. Consumption: 3.2 A


Dimensions: 160x115x25 mm Weight: 250 g



Compatible with CI-BUS systems



FlatSat WiFi
OPTIONS – TWIN for 2 receivers
Weight: approx. 9,0 kg
Dish dimensions: 63,5x59 cm



- 1) The compact, watertight housing contains a WLAN Internet antenna and a cable guide with 2 or 3 holes for the satellite antenna cables.
- 2) Mobile Internet antenna: TAW85 reception frequency: 700-6000 MHz
For 5G-4G-3G-WLAN signals
Gain: 6 dBi Max
- 3) 5 mm cable cross section, 5 m cable length with SMA connector for connection to the WLT24EX2 router
- 4) Dimensions: 121x63x84 mm

FLATSAT CLASSIC BT

FULL HD

Flatsat Classic BT consists of:

- 1 External satellite antenna
- 1 DVB-S2 Control unit complete with leads
- 1 Control panel



Automatic Satellite Antenna HD with 16 saved Satellites. Equipped with DVB-S2 control unit with OLED display and 2 keys to start a satellite search or lower the dish. Can also be controlled via Bluetooth from your Smartphone via the TELECO App. The control unit also features a CI Bus port. All software updates - when made available on the TELECO App - can, in fact, be loaded directly by the user from a smartphone via Bluetooth. The Flatsat Classic BT is compatible with all TVs equipped with a DVB-S2 tuner and all Satellite receivers. Safety system with automatic closing of the antenna when the vehicle is started



- Wall-mounted control panel with just two keys and display

Optional:

SMART

- SMART function When the user changes channel with the TV remote control the antenna automatically points itself at the satellite broadcasting the selected channel.




DVB-S2 HD Control Unit
 Power supply 12/24 V DC (10-31 V DC)
 Max. Consumption: 3.2 A
 Dimensions: 160X115X25 mm Weight: 250 g




Compatible with CI-BUS systems




Android



Flatsat Classic BT 50
 OPTIONS – TWIN: for 2 receivers
 Weight: about 8.8 kg
 Dish dimensions: 49x45.5 cm



Flatsat Classic BT 65
 OPTIONS – TWIN: for 2 receivers
 Weight: about 9.0 kg
 Dish dimensions: 63.5x59 cm



Flatsat Classic BT 85
 OPTIONS – TWIN: for 2 receivers
 Weight: about 10.8 kg
 Dish dimensions: 85x78 cm

TELESAT BT

FULL HD

Telesat BT consists of:

- 1 External satellite antenna
- 1 DVB-S2 Control unit complete with leads
- 1 Control panel

Convenient choice!



HD Automatic Satellite Antenna with 16 saved satellites. Equipped with a DVB-S2 control unit with OLED display and two buttons to start a satellite search or lower the dish. Can also be controlled with a Smartphone via Bluetooth using the TELECO App. The control unit is also equipped with a CI Bus port. When made available on the TELECO App, all software updates can be uploaded directly with a smartphone via Bluetooth. The Flatsat Easy BT is compatible with all TVs equipped with the DVB-S2 tuner and all satellite receivers. Safety system with automatic closing of the antenna when the vehicle is started.



- Wall-mounted control panel with just two keys and display

Optional:

SMART

- SMART function When the user changes channel with the TV remote control the antenna automatically points itself at the satellite broadcasting the selected channel.


Bluetooth

DVB-S2 HD Control Unit
Power supply 12/24 V DC (10-31 V DC)
Max. Consumption: 3.2 A
Dimensions: 160X115X25 mm Weight: 250 g



Compatible with CI-BUS systems



Telesat BT 65
OPTIONS – TWIN: for 2 receivers
Weight: approx. 9.0 kg
Dish dimensions: 63.5x59 cm




Telesat BT 85
OPTIONS – TWIN: for 2 receivers
Weight: about 10.6 kg
Dish dimensions: 85x78 cm

FLATSAT EASY BT

FULL HD

Flatsat Easy BT consists of:

- 1 External satellite antenna
- 1 DVB-S2 Control unit complete with leads
- 1 Control panel



Automatic Satellite Antenna HD with 16 saved Satellites. Equipped with DVB-S2 control unit with OLED display and 2 keys to start a satellite search or lower the dish. Can also be controlled via Bluetooth from your Smartphone via the TELECO App. The control unit also features a CI Bus port. All software updates - when made available on the TELECO App - can, in fact, be loaded directly by the user from a smartphone via Bluetooth. The Flatsat Easy BT is compatible with all TVs equipped with a DVB-S2 tuner and all Satellite receivers. Safety system with automatic closing of the antenna when the vehicle is started.



- Wall-mounted control panel with just two keys and display

Optional:




- SMART function When the user changes channel with the TV remote control the antenna automatically points itself at the satellite broadcasting the selected channel.




DVB-S2 HD Control Unit
 Power supply 12/24 V DC (10-31 V DC)
 Max. Consumption: 3.2 A
 Dimensions: 160X115X25 mm Weight: 250 g



Compatible with CI-BUS systems



Flatsat Easy BT 70
 OPTIONS – TWIN for 2 receivers
 QUAD: for 4 receivers
 Weight: about 10.5 kg
 Dish dimensions: 72x67 cm



Flatsat Easy BT 90
 OPTIONS – TWIN for 2 receivers
 QUAD: for 4 receivers
 Weight: about 11.6 kg
 Dish dimensions: 91x85 cm

FLATSAT EASY SKEW BT SMART



SMART

FULL HD

Flatsat Easy Skew BT Smart consists of:

- 1 External satellite antenna
- 1 DVB-S2 Control unit complete with leads
- 1 Control panel



Automatic Satellite Antenna HD with 16 saved Satellites. Equipped with DVB-S2 control unit with OLED display and 2 keys to start a satellite search or lower the dish. Can also be controlled via Bluetooth from your Smartphone via the TELECO App. Alternatively, the wall-mounted control panel with just two keys and display can be used. The control unit also features a CI Bus port. The antenna that's SMART! When the user changes channel with the TV remote control the antenna automatically points itself at the satellite broadcasting the selected channel.

All software updates - when made available on the TELECO App - can, in fact, be loaded directly by the user from a smartphone via Bluetooth. Flat-Sat Easy Skew is compatible with all TVs equipped with a DVB-S2 tuner and with all Satellite receivers. Safety system with automatic closing of the antenna when the vehicle is started.



DVB-S2 HD Control Unit

Power supply 12/24 V DC (10-31 V DC)

Max. Consumption: 3.2 A

Dimensions: 160X115X25 mm Weight: 250 g



Compatible with CI-BUS systems



Flatsat Easy Skew BT SMART 70
OPTIONS – TWIN for 2 receivers
Weight: approx. 10.8 kg
Dish dimensions: 72x67 cm



Flatsat Easy Skew BT SMART 90
OPTIONS – TWIN for 2 receivers
Weight: approx. 12.0 kg
Dish dimensions: 91x85 cm

ACTIVSAT SMART

Fully Automatic Portable Satellite System

You can park your caravan or camper van in the shade of a tree and install your ACTIVSAT automatic system alongside it on the lawn.

Simply open the tripod, fit the motor unit on top of it, slide in the dish and connect the cable (15 m) to the external Activsat socket on the vehicle.

Very quick and easy installation, no tools needed.

Align with the satellite in just a few seconds

via Bluetooth through your smartphone, or simply by pushing a button on the control box inside your vehicle.

Every time the ACTIVSAT aligns with a satellite, the position is stored in its memory to save time when the next search is made..

iOS

Android

Bluetooth

CI BUS



COMPASS establishes the exact position of the antenna in real time, thus making it easier to position the latter in the direction of the desired satellite

SKEW indicates, on the basis of the position of the antenna and the selected satellite, whether the LNB needs rotating.



Small, sleek-looking indoor unit equipped with:



- 1) 16 satellites stored in memory
- 2) High definition blue OLED graphic display
- 3) SAT Button / Quick Search Button / Park Button
- 4) Incorporated Bluetooth to control your ACTIVSAT directly from your Smartphone
- 5) Anti-theft alarm with very loud beeper (91 dB) with ON-OFF switch.
- 6) CI BUS port for connection to CI BUS system
- 7) Additional output to connect to a powerful external siren (optional) or external light
- 8) ON-OFF power switch
- 9) Quick, user-friendly software updates via Bluetooth with your smartphone

Double Anti-theft Alarm:

1) If somebody cuts the cable, a very loud beeper will go off. An external light and siren can be automatically switched on (optional).

2) The external antenna is strictly associated with its internal control unit through the Serial Number. All SNs are stored in a Teleco database. If somebody steals the outdoor unit, they will not be able to obtain as spare control unit without providing the SN of the antenna and their name!

Five Models available:

1) ACTIVSAT 85	Kg 10,40
2) ACTIVSAT 85T Twin	Kg 10,40
3) ACTIVSAT 65	Kg 8,50
4) ACTIVSAT 65T Twin	Kg 8,50
5) ACTIVSAT 53SQ	Kg 10,50

ActivSat bags (optional)

All components are easily stored and transported thanks to 2 hard-wearing bags: one for the dish, and one for the outdoor unit with tripod and cable.

MODELS:

- BAS/TR - Tripod bag
- BAS/65 - Ø65 dish bag
- BAS/85 - Ø85 dish bag
- BAS/65 - Square antenna bag



External socket for activsat

(optional)



Mod. PAS/F FAWO



Mod. PAS/W WESTACC



SE110C - EXTERNAL SIREN
(optional)
12 Vdc - 110 dB

SPECIFICATIONS

Material: ABS

Colour: white outside,
black inside

INPUTS:


- connector for 10-pole ActivSat motor cable
- F connector for ActivSat coaxial cable
- F connector for second coaxial cable (ActivSat Twin)
- F connector for coaxial cable for external TV
- 12 V DC universal socket (Max 10 A) with rubber cover and Faston terminals for external TV power supply

AVAILABLE MODELS:

- PAS/W - ActivSat Westacc socket
- PAS/F - ActivSat Fawo socket



MANUAL AND SEMI-AUTOMATIC



Manually aligned satellite antenna. The antenna that lets users find the satellite manually with ease..

New wall mounting clamp




Are you unable or unwilling to install an automatic satellite antenna on the roof? Then the Voyager series is the right choice for you. This antenna allows you to easily find the right satellite from inside your motorhome or caravan. While travelling, the dish is fully folded back on the roof.

- Height when folded is just 17-18 cm.
- The lightweight aluminium arm firmly supports the satellite antenna, offers better wind resistance and provides an excellent signal reception surface.
- Fully equipped and totally watertight passage through the roof.
- Corrosion resistant anodised aluminium mast with internal locking system.
- Satellite alignment accuracy is ensured by a fully watertight, high-precision mechanical reduction gear in oil bath.

Footprint: advice on choosing a satellite dish

Reception of television and radio signals is guaranteed within the coloured areas (footprints). Cloud cover and rain could negatively affect reception of the satellite signal. So it is important, when choosing your satellite system, to check carefully that the dimensions of the dish are sufficient to receive a good satellite signal in the places that you will be visiting.



Footprint legend

85cm

65cm

50cm




SATELLITE ANTENNAS



VOYAGER G3

VOYAGER DIGIMATIC

MOTOSAT DIGIMATIC

HD/TV		✓	✓	✓
Digital tilt		✓	✓	✓
Electronic inclination				✓
LNB protective cover		For 65 and 85cm dish	For 65 and 85cm dish	
Mast length		33cm of 52cm	33cm of 52cm	33cm of 52cm
				
Digital satellite search			✓	✓
DSF90E:				
Number of satellites			8	8
Signal quality indicator			✓	✓
Digital tilt indicator			✓	✓
Dimensions when closed	50cm			
	65cm			
	85cm			
Weight (approx.)	50cm	6.8kg	6.8kg	
	65cm	9.2kg	9.2kg	8.0kg
	85cm	11.4kg	11.4kg	10.2kg
Dish dimensions	50cm	49x45.5 cm	49x45.5 cm	
	65cm	72x67cm	72x67cm	63.5x59cm
	85cm	91x85 cm	91x85 cm	85x78 cm

VOYAGER G3



FULL HD

New wall mounting clamp



Manual satellite antenna with graduated scale on the mast

Voyager G3 has a graduated scale on the mast for quickly setting the inclination when aligning the dish, a task that can be carried out from inside the vehicle. In order to set the inclination correctly it is important that the vehicle is level, otherwise the angle of the vehicle will have to be added to or taken away from the inclination value of the dish. After having set the inclination, just rotate the dish southward by turning the mast from the inside and adjust the positioning by watching the picture on the screen. Would you like it to be even easier? Then maybe the Voyager Digimatic is the one for you.

CONTENTS OF EACH VOYAGER G3 KIT

- Satellite antenna complete with fold-down mast and connection cables
- Universal LNB
- Parabolic dish
- A detailed instruction manual

Long mast 52 cm



Voyager G3 50:
with dish
49x45.5 cm

Voyager G3 65:
with dish
72x67 cm

Voyager G3 85:
with dish
91x85 cm


Short mast 33 cm



Voyager G3 SM 50:
with dish
49x45.5 cm

Voyager G3 SM 65:
with dish
72x67 cm

Voyager G3 SM 85:
with dish
91x85 cm



VOYAGER DIGIMATIC



The Voyager Digimatic and Voyager G3 share the same design, but the former is equipped with a digital pointer and an electronic inclinometer.


With Voyager Digimatic the user can align the dish with the satellite desired manually in just a few quick and simple steps. Currently, the biggest difficulty in manually aligning a dish with a satellite broadcasting digital TV signals is the fact that there is a delay before the digital signals are displayed on LCD TV screens, and so the user is forced to carry out the alignment with a very slow movement in order to avoid the risk of going past the required satellite without realising it.

Voyager Digimatic is the solution to this problem. It is equipped with an electronic elevation meter that sends a reading to the display of the actual absolute value of the inclination of the dish, even if the vehicle is not level. The DSF90E/HD that is included indicates (directly) both the elevation and the strength of the signal. This makes it possible to quickly align this manual dish system with the desired satellite without the disadvantage of delayed signals.

DVB S2
FULL HD


CONTENT OF EACH VOYAGER DIGIMATIC KIT

- Satellite antenna complete with fold-down mast and connection cables
- Universal LNB
- DSF90E/HD digital satellite finder
- Parabolic dish
- A detailed instruction manual



DSF90E/HD

How to use the DSF90E/HD



- 1) Select the satellite for the alignment (e.g. ASTRA 23).
- 2) Raise the dish until the correct elevation is indicated (see the elevation map).
- 3) Turn the dish SOUTHWARDS until the DSF90E/HD emits a continuous "BEEP".
- 4) Wait for the SAT OK LED to come on.
- 5) If alignment has been made with the wrong satellite, the SAT NOT OK LED will come on and the dish must be rotated again until the "BEEP" is heard again and the SAT OK LED comes on.
- 6) When the maximum number of LEDs are illuminated on the LEVEL indicator, the dish has been aligned properly.

Long mast 52 cm



Voyager Digimatic 50:
with dish
49x45.5 cm

Voyager Digimatic 65:
with dish
72x67 cm

Voyager Digimatic 85:
with dish
91x85 cm




Short mast 33 cm

Voyager SM Digimatic 50:
with dish
49x45.5 cm

Voyager SM Digimatic 65:
with dish
72x67 cm

Voyager SM Digimatic 85:
with dish
91x85 cm



MOTOSAT DIGIMATIC

Basically the MotoSat Digimatic is the same as the MotoSat but is equipped with a digital aligner and an electronic inclinometer.

With MotoSat Digimatic the user can align the dish manually with the satellite desired in just a few quick and simple steps. Currently, the biggest difficulty in manually aligning a dish with a satellite broadcasting digital TV signals is the fact that there is a delay before the digital signals are displayed on LCD TV screens, and so the user is forced to carry out the alignment with a very slow movement in order to avoid the risk of going past the required satellite without realising it.

MotoSat Digimatic is the solution to this problem. In addition to an electronic elevation controller, it is equipped with an electronic elevation meter that sends a reading to the display of the actual absolute value of the inclination of the dish, even if the vehicle is not level. The DSF90E/HD that is included indicates (directly) both the elevation and the strength of the signal. This makes it possible to quickly align this manual dish system with the desired satellite without the disadvantage of delayed signals.

12 Volt
electric
motor

DVB S2

FULL HD



DSF90E/HD

How to use the DSF90E/HD



1) Select the satellite for the alignment (e.g. ASTRA 23). 2) Raise the dish until the correct elevation is indicated (see the elevation map). 3) Turn the dish SOUTHWARDS until the DSF90E/HD emits a continuous "BEEP". 4) Wait for the SAT OK LED to come on. 5) If alignment has been made with the wrong satellite, the SAT NOT OK LED will come on and the dish must be rotated again until the "BEEP" is heard again and the SAT OK LED comes on. 6) When the maximum number of LEDs are illuminated on the LEVEL indicator, the dish has been aligned properly.



Long mast 52 cm

MotoSat
Digimatic 65

MotoSat
Digimatic 85



Short mast 33 cm

MotoSat
Digimatic SM 65

MotoSat
Digimatic SM 85

Kg 8,0

◀ 80 cm ▶



MotoSat 65 Digimatic
with 63.5 x 59 cm dish

▲
16 cm
▼

Kg 10,2

◀ 101 cm ▶



MotoSat 85 Digimatic
with 85 x 78 cm dish

▲
16 cm
▼

CARRY SAT

Portable satellite dish with manual alignment

FULL HD

A portable satellite kit that is easy to set up and dismantle.

Requires only minimal storage space.

The Carry Sat has been designed for rapid set-up and dismantling. The pre-assembled dish has a fold-down LNB arm and a two-part clamp to attach the mast, which reduces the time it takes to put the whole kit back in the locker to just a few seconds. It works with all types of satellite receivers.

To simplify alignment, we recommend using DSF90 HD.



Kit content:

- Aluminium tripod (TP3 ALU) with umbrella opening and closing action equipped with a rotating upper section for easy alignment of the dish.
- Pre-assembled satellite dish of either 65 or 80 cm with fold-down LNB support arm
- Low noise universal LNB
- 10 m lead with connectors
- 3 pegs for securing Carry Sat to the ground

Available Models:

- CARRY SAT ALU 80 with 80 cm dish
- CARRY SAT ALU 65 with 65 cm dish
- The tripod is also available on its own, model TP3ALU



DSF90 HD

DSF90E HD

DVB S2

Digital satellite precision aligners




The DSF90 HD is compatible with all the manual satellite systems and enables the user to find the desired satellite in just a few quick and simple steps.

Currently, the biggest difficulty in manually aligning a dish with a satellite broadcasting digital TV signals is the fact that there is a delay before the digital signals are displayed on LCD TV screens, and so the user is forced to carry out the alignment with a very slow movement in order to avoid the risk of going past the required satellite without realising it.

The DSF90 HD is the solution to this problem. It has a meter that indicates immediately the strength of the signal being received from the desired satellite. Unlike ordinary dish aligners, there is no delay and, again unlike those systems, the DSF80 also tells you if the satellite you have found is the right one. There are 8 satellites pre-programmed in its memory.

The DSF90E/HD is the same as the DSF90 HD, but is specifically designed for Teleco Digimatic systems with incorporated electronic elevation detector.

As well as the functions described for the DSF90 HD, the DSF90E/HD also provides the effective elevation.



PROCEDURE

- 1) Select the satellite for the alignment (e.g. ASTRA 23).
- 2) Raise the dish until the correct elevation is indicated (see the elevation map).
- 3) Turn the dish SOUTHWARDS until the DSF90E/HD emits a continuous "BEEP".
- 4) Wait for the SAT OK LED to come on.
- 5) If alignment has been made with the wrong satellite, the SAT NOT OK LED will come on and the dish must be rotated again until the "BEEP" is heard again and the SAT OK LED comes on.
- 6) When the maximum number of LEDs are illuminated on the LEVEL indicator, the dish has been aligned properly.

ACCESSORIES

CGU2

2-USB battery charger for campers



Features

Input: 12V/24V (9-36V) DC

Output: 5V 2.1A

- 2 USB sockets to charge mobile phone and TKB25 wireless speaker kit simultaneously
- 12/24 DC connector with red adapter for cigarette lighter and vehicle internal light socket.



Motosat Kit

This kit transforms an existing manual Voyager system into a semiautomatic system.



Now the dish's inclination can be adjusted using two buttons; the display shows the correct inclination to help you find the desired satellite as quickly as possible.



SPCP

Plastic rooftop cable holder box



SPCA

Aluminium lead-through box for the roof



SPC64 - Black
Narrow plastic rooftop
cable holder box

SPC64

Narrow plastic rooftop
cable holder box

CAM Modules



Tivusat HD CAM module
with Smart Card included
for watching Tivusat (also HD)
satellite programmes
with TELECO televisions



FRANSAT HD CAM module
with SMART CARD for France only
suitable for TELECO TVs

SMART TV



SMART TV

Internet directly on the TV of your Camper or Caravan with TELECO SMART TVs

Your TV transformed into a MEGA Smartphone with incorporated Wi-Fi.

Your TV transformed into a MEGA Smartphone with incorporated WI-FI. You can connect directly to a portable Wi-Fi Router with SIM Card (e.g. WIFI VAN T402) and use the Internet directly via the remote control.

Download the most popular Apps and connect to your favourite social media: FaceBook, Instagram, WhatsApp, YouTube etc. Perform Google searches and download films and Video games. You can also watch your favourite NETFLIX series.

With the supplied Miracast App you can transfer photos and videos directly from your smartphone to the TV and enjoy them on a much larger screen.

Ready to receive DVB-S2 satellite, DVB-T2 HEVC terrestrial and DVB-C cable programmes

Power supply: 12-24 Volt from battery and 230 V AC from mains power ON-OFF switch

Remote control with two additional keys to pilot the Teleco automatic satellite antenna

5000 satellite channels - 1000 TV channels

Preset satellite channel lists for most European countries: Germany, France, Holland-Belgium, Switzerland, Italy, Austria, Norway, Sweden, Finland, Denmark, Croatia, Hungary, Romania, Slovenia etc.

DVB S2 DVB T2 HEVC 10 Bit DVB C FULL HD M7 Group FRANSAT TELEVISION NUMERIQUE CI+




Remote control function

You can control the antennas with TEK TV remote controls via the ON and PARK buttons

SMART TV



You can control the antennas with TEK TV remote controls via the ON and PARK buttons



MODEL	TEK15 W9 SMART	TEK19E W13 SMART	TEK22E W13 SMART
PANEL			
Screen Size (diagonal)	15,6 " TFT-LED	19 " TFT-LED	21.5" TFT-LED
Backlight	ELED	ELED	ELED
Resolution	1920x1080	1366x768	1920x1080
Response Time (typical)	15ms	14ms	7ms
Brightness (cd/m2, typical)	200cd/m2	200cd/m2	220cd/m2
Contrast Ratio (typical)	1500:1	1000:1	3000:1
Viewing Angle Degree (H/V)	H:170°, V:170°	H:178°, V:178°	H:178°, V:178°
Frame Rate	60Hz	60Hz	60Hz
Aspect Ratio	16:9	16:9	16:9
TV System			
Support H.265	YES	YES	YES
Teletext	1000 pages	1000 pages	1000 pages
Noise Reduction	YES	YES	YES
Bluetooth Version	V4.2	V5.2	V5.2
Android solution	Android 9.0	Android 13	Android 13
AUDIO			
Audio Output	2*5W	2*5W	2*5W
INPUTS AND OUTPUTS			
TV Tuner	x2	x2	x2
RJ45	x1	x1	x1
CI +	x1	x1	x1
COAX	x1	x1	x1
HDMI	x2 (CEC,ARC, MHL)	x3 (CEC,ARC, MHL)	x3 (CEC,ARC, MHL)
USB	x2	x2	x2
EARPHONE	x1	x1	x1
AV IN (MINI)	x1	x1	x1
RL AUDIO out	x1	x1	x1
POWER CONSUMPTION			
Power Supply	AC100V-240V DC 9-32V	AC100V-240V DC 10-30V	AC100V-240V DC 10-30V
Power Consumption (W)	<18W	<13W	<36W
Standby Power Consumption	<0.5W	<0.5W	<0.5W
REMOTE FEATURE			
EPG	YES	YES	YES
Sleep Timer	YES	YES	YES
ACCESSORIES			
Remote Control	YES	YES	YES
Mini AV lead	YES	NO	NO
Cigarette lighter	YES	NO	NO
Power Cord & Adaptor	YES	NO	NO
CASE			
Cabinet Colour	Black	Black	Black
Desk Top Stand	YES	YES	NO
Vesa Pattern	100x100mm	100x100mm	100x100mm
DIMENSIONS			
Net weight (kg)	1,6	2,2	2,5
Gross weight (kg)	2,3	3,1	4,1
Product Dimensions without stand (mm)	376 x 240 x 54 mm	436 x 266 x 49 mm	501 x 304 x 49 mm



TEK24E W11 SMART	TEK32E W11 SMART	TEK40S SMART
24" TFT-LED	31.5" TFT-LED	39.5" FHD
ELED	ELED	ELED
1920x1080	1920x1080	1920x1080(1080p)
5ms	8ms	8ms
200cd/m2	200cd/m2	250cd/m2
3000:1	1200:1	1000:1
H:178°, V:178°	H:178°, V:178°	H:178°, V:178°
60Hz	60Hz	60Hz
16:9	16:9	16:9
YES	YES	YES
1000 pages	1000 pages	1000 pages
YES	YES	YES
V4.2	V4.2	V4.2
Android 11	Android 11	Android 7.0.1 OS
2*5W	2*10W	2*10W
x2	x2	x2
x1	x1	x1
x1	x1	x1
x1	x1	x1
x2 (CEC, ARC, MHL)	x2 (CEC, ARC, MHL)	x2 (CEC, ARC, MHL)
x2	x2	x4
x1	x1	x1
x1	x1	x1
x1	x1	x1
AC100V-240V	AC100V-240V	AC100V-240V
DC 9-32V	DC 10-32V	DC 11.30-30V
<35W	<50W	<85W
<0.5W	<0.5W	<0.5W
YES	YES	YES
YES	YES	YES
YES	YES	YES
NO	NO	YES
NO	NO	YES
NO	NO	YES
Black	Black	Black
NO	NO	YES
100x100mm	100x100mm	200x200mm
2,9	5,1	5,6
4,3	7,3	6,5
549 x 323 x 49	725 x 442 x 65 mm	909 x 517 x 62 mm

TKB25 - Kit

The Kit consists of a small wireless Audio Transmitter, easily applicable to every Teleco TV, and a high quality wireless Speaker able to reproduce and boost, via wireless, the audio level of your Teleco TV. The wireless Speaker can also be used to play Music from a Smartphone



TKB25
How to increase the Audio Level of your TV with the Teleco wireless kit.

TELEVISIONS **LED** for campers and caravans



New-concept TEK TVs have a Wide Viewing Angle (178°x178°), a DVB-S2 satellite input and DVB-T2 HEVC terrestrial input + Cable. They are equipped with special software that automatically associates every country with its programme list. So if the user selects Germany, he/she will automatically be given a list of German programmes; if France is selected the list of French programmes is provided and so on. This makes setting up the TV in the factory or at the dealership quick and easy. For all campers going to France the country France is selected and the French programme list is automatically loaded. For those going to Germany the German list is selected and so on.



You can control the antennas with TEK TV remote controls via the ON and PARK buttons



12 Volt TELEVISIONS

TEK22D**TEK22DE**

with DVD without stand

TEK22E

without DVD and stand

22" HD TV FOR CARAVANS AND MOTORHOMES
WITH DVD PLAYERDVB-S2 SATELLITE RECEIVER WITH
INTEGRATED DVB-T2 HEVC TERRESTRIAL
RECEIVERFRANSAT AND M7 WITH
FAST SCAN FUNCTION**FULL HD****DVB S2****DVB T2 HEVC 10 Bit****DVB C****9-32
Vdc**

- 9 - 32 V DC or 230 V AC power supply
- DVD reader
- USB port with PVR Multimedia function to play video and audio content
- 21.5" FHD screen (56 cm diagonal)
- 5,000 satellite and 1000 terrestrial channels with LCN
- OSD in 8 languages
- Teletext
- Timer
- Parental Lock
- Audio power 2.5 W with equalizer

CONNECTIONS

- 2 HDMI sockets
- 1 SCART socket
- 1 AV input for headphones
- 1 AV IN input
- 1 YPBPR socket (Mini)
- 1 CI+ port
- 1 RL Audio Out socket
- 2 USB multimedia ports
- 1 power socket
- 9 - 32 V DC
- 1 ON-OFF switch

TECHNICAL SPECIFICATIONS

- 1 WGA resolution (1920x1080)
- Viewing angle H178°, V178°
- 1 Brightness 200 CD/m²
- 1 Contrast 1000:1
- 1 Response time 5 mS
- DVB-S2 satellite
- DVB-T2 H.265 terrestrial

Weight: 2.8 kg
Dimensions without feet:
507 x 50 x 310 mm



You can control the antennas with TEK TV remote controls via the ON and PARK buttons

TEK24D24" HD TV FOR CARAVANS AND
MOTORHOMES WITH DVD PLAYERDVB-S2 SATELLITE RECEIVER WITH
INTEGRAL DVB-T2 HEVC TERRESTRIAL
RECEIVERFRANSAT AND M7 WITH
FAST SCAN FUNCTION**FULL HD****DVB S2****DVB T2 HEVC 10 Bit****DVB C****9-32
Vdc**

- 9 - 32 V DC or 230 V AC power supply
- DVD reader
- USB port with PVR Multimedia function to play video and audio content
- 24" FHD screen (60 cm diagonal)
- 5,000 satellite and 1000 terrestrial channels with LCN
- OSD in 8 languages
- Teletext
- Timer
- Parental Lock
- Audio power 2.5 W with equalizer

CONNECTIONS

- 2 HDMI sockets
- 1 SCART socket
- 1 AV socket for headphones
- 1 AV input
- 1 YPBPR socket (Mini)
- 1 CI+ port
- 1 RL Audio Out socket
- 2 USB multimedia ports
- 1 power socket 9 - 32 V DC
- 1 ON-OFF switch

TECHNICAL SPECIFICATIONS

- WGA resolution (1920x1080)
- Viewing angle H178°, V178°
- 1 Brightness 200 CD/m²
- 1 Contrast 1000:1
- 1 Response time 5 mS
- DVB-S2 satellite
- DVB-T2 H.265 terrestrial

Weight: 2,5 kg
Dimensions without feet:
507 x 50 x 310 mm



You can control the antennas with TEK TV remote controls via the ON and PARK buttons

DVB-T2 TERRESTRIAL ANTENNAS



TELEPLUS X2

The design and production of this antenna stems from the experience and great success achieved in recent years with the TELEPLUS antenna.

DVB T2 HEVC
ULTRA HD 4K

FILTER
5G

DAB+
Digital Audio Broadcasting

FILTER
LTE

**Dual
polarity
38db**

Great care has been given to increasing the gain curve resulting in an even higher sensitivity to weak signals. The introduction of the POLARITY ORIENTATION MECHANISM also allows you to get the best reception of all TV signals (digital and analogue) that are transmitted with both HORIZONTAL and VERTICAL polarity. (With the advent of digital transmission, signals with VERTICAL polarity are enhanced in certain countries such as Italy and Britain). A low noise amplifier is included; this has a variable gain that operates at both 12 and 24 V DC.



Zamak mechanism for
HORIZONTAL and VERTICAL
polarity adjustment from inside
the vehicle

Wedge shaped spacer
for perfect adaptation
to any roof shape

Simple, safe mast lock
system

TELEPLUS X2/39U

- UHF
- Dual polarity
- High 38 dB gain (with amplifier)

Gain with amplifier:: 38 dB channels 21-48 (UHF)

Power supply: 12 V DC-24 V DC.

with 39 cm mast for installation inside a suspended wall unit.

Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones. (Only for countries that have already incorporated LTE transmissions in the 700 - 800 MHz band).

Horizontal
reception
diagram



ULTRA HD
4K

FILTER
5G

FILTER
LTE

DVB T2 HEVC
DAB+
Digital Audio Broadcasting



TELEPLUS X2

Teleplus X2 /165VU

Teleplus X2 /110VU

Teleplus X2 /5 1VU

- VHF - UHF
- Dual polarity
- High 38 dB gain (with amplifier)

Gain with amplifier::

38 dB channels 21-48 (UHF)

22 dB channels E5 - E12 (VHF BIII)

Power supply: 12 V DC-24 V DC.

Teleplus X2/165 VU: with 165 cm mast

Teleplus X2/110 VU: with 110 cm mast

Teleplus X2/51 VU: with 51 cm mast

Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones. (Only for countries that have already incorporated LTE transmissions in the 700 - 800 MHz band).

Horizontal
reception
diagram



ULTRA HD
4K

FILTER
5G

FILTER
LTE

DVB T2 HEVC
DAB+
Digital Audio Broadcasting



TELEPLUS 3G



DVB T2 HEVC
ULTRA HD 4K

DAB+
Digital Audio Broadcasting

Directional antenna for 36 dB digital terrestrial signals

FILTER
5G

FILTER
LTE

Equipped with LTE suppressor filter



- High Gain for reception of even the weakest signals
- Exceptionally good directional adjustment to suppress noise
- Zamak mast connector
- Gain with variable amplifier: UHF 36 dB - VHF-B3 22 dB - VHF-B1 20 dB
- Powered at 12/24 Volts
- Recommended that it be used with SF165 telescopic mast (optional)

Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones. (Only for countries that have already incorporated LTE transmissions in the 700 - 800 MHz band).

Kit content:

- 1 antenna UHF - VHF (B3)
- 1 adjustable-gain amplifier with 3 TV outputs + a DAB and FM output
- 1 Ø 30 mast connector with 5 m cable



TELESCOPIC MAST FOR MOTORHOMES AND CARAVANS



Enables you to easily re-orientate your TV antenna without having to leave the vehicle. Water-tight fit guaranteed by double O-ring system. Corrosion-resistant anodised aluminium. Fully equipped for connection to any type of antenna.

TECHNICAL SPECIFICATION

- SF 50: Length: 50 cm
- SF 165: Length: 165 cm
- Diameter: from 30 to 34 mm (can be adjusted)
- SF 165: Weight: 1.1 kg
- SF 50: Weight: 0.5 kg

Teleplus

Directional antennas for DVB-T2 digital terrestrial signals



Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones. (Only for countries that have already incorporated LTE transmissions in the 700 - 800 MHz band).

Technical specifications
 Channels: 5 - 12 21 - 48
 Gain with amplifier: (dB) 22 36
 Power supply type: 12 / 24 V
 Length: 50.5 cm
 Width: 40 - 70 cm
 Weight: 1.8 kg

Package contents
 TV Antenna with attachment bracket for mast, with diameter of 25 to 50 mm
 1 Adjustable-gain amplifier with 2 TV outputs +1 Radio DAB and FM output
 5 metres of 75 Ohm coaxial cable with three F connectors.



Omnidirectional antennas for DVB-T2 terrestrial digital signals

Weekend Super



Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones. (Only for countries that have already incorporated LTE transmissions in the 700 - 800 MHz band).

Technical specifications
 Channels: 5 - 12 21 - 48
 Gain with amplifier: (dB) 9 26
 Power supply type: 12 / 24 V
 Diameter: 28 cm
 Height: 12 cm
 Weight: 0.7 kg

Package contents
 1 TV Antenna with universal bracket for attachment to roof or mast (Ø 32-34 mm)
 1 Adjustable-gain amplifier with 2 TV outputs +1 Radio DAB and FM output
 5 metres of 75 Ohm coaxial cable
 Three F connectors



Omnidirectional antennas for DVB-T2 terrestrial digital signals

Yachting 11



Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones. (Only for countries that have already incorporated LTE transmissions in the 700 - 800 MHz band).

Technical specifications
 Channels: 5 - 12 21 - 48
 Gain with amplifier: (dB) 16 26
 Power supply type: 12 / 24 V
 Diameter: 38 cm
 Height: 16.5 cm
 Weight: 1.4 kg

Package contents
 1 TV Antenna with universal bracket for attachment to roof or on mast (Ø 32-34 mm)
 1 Adjustable-gain amplifier with 2 TV outputs +1 Radio DAB and FM output
 5 metres of 75 Ohm coaxial cable
 Three F connectors



Omnidirectional antennas for DVB-T2 terrestrial digital signals

Walkie 22



Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones. (Only for countries that have already incorporated LTE transmissions in the 700 - 800 MHz band).

Channels: 5 - 12 21 - 48
Gain with amplifier (dB): (dB) 22 26
Power supply type: 12 / 24
Diameter: 38 - 88 cm
Height: 16.5 cm
Weight: 1.4 kg

Package contents
 1 TV antenna with universal support for attachment on roof or mast (Ø 32-34 mm)
 1 Adjustable-gain amplifier with 2 TV outputs +1 Radio DAB and FM output
 5 metres of 75 Ohm coaxial cable
 Three F connectors



WING • WING 11 • WING 22

Omnidirectional TV antennas for high speed camper vans

The Wing, Wing 11 and Wing 22 series of antennas have been designed to receive all digital terrestrial signals. Particular attention was given to creating an ultra-aerodynamic shape to enable it to be installed on the fastest of motorhomes. It is also equipped with a special, ergonomic foot that allows the antenna to be tilted in any direction, thus making it easy to install on even the most streamlined roofs of latest generation motorhomes and caravans.

DVB T2 HEVC
ULTRA HD 4K

FILTER
LTE 5G



3-axis rotation for optimal alignment with respect to the roof, thus allowing easy installation also on latest-generation motorhomes and caravans



Wing Digital Terrestrial

The MINI antenna (just 31 cm diameter) specially designed to receive UHF channels. A special configuration of the circuit combined with a high gain amplifier enables reception of VHF B3 programmes too.



Omni-directional antennas 360° 26 dB UHF – 9 dB VHF- B3

Horizontal
reception
diagram



Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones..

Gain with amplifier::

CH 5-12 9 dB

CH 21-48 26 dB

Power supply: 12/24 Volt

Diameter: 31 cm

Height: 16.5 cm

Weight: 1 kg

Package contents

1 Antenna, complete with 5 m coax cable and 3 F connectors

1 Adjustable gain amplifier, with 2 outputs for 3 TV+1 Radio DAB and FM output, operating at 12 and 24 V DC

Wing 11 Digital Terrestrial

The high sensitivity of the electronic amplifier combined with a special antenna design lets you receive TV programmes at lower frequencies while keeping external dimensions to just 38 cm.



Omni-directional antennas 360° 26 dB UHF 16 dB VHF- B3

Horizontal
reception
diagram



Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones.

Gain with amplifier::

CH 5-12 16 dB

CH 21-48 26 dB

Power supply: 12/24 Volt

Diameter: 38 cm

Height: 19.5 cm

Weight: 1.2 kg

Package contents

1 Antenna, complete with 5 m coax cable and 3 F connectors

1 Adjustable gain amplifier, with 2 outputs for 3 TV+1 Radio DAB and FM output, operating at 12 and 24 V DC

Wing 22 Digital Terrestrial

The combining of two antennas has resulted in this DUAL POWER antenna that provides excellent performance levels even for programmes on lower frequencies (VHF - B3). In addition, the use of a low-noise amplifier enables reception of even very weak signals.



Omni-directional antennas 360° 26 dB UHF 22 dB VHF- B3



Horizontal
reception
diagram

Equipped with LTE Suppressor Filter to eliminate any disturbance caused by new 4G / 5G Smartphones.

Gain with amplifier::

CH 5-12 22 dB

CH 21-48 28 dB

Power supply: 12/24 Volt

Diameter: 38 - 88 cm

Height: 19.5 cm

Weight: 1.4 kg

Package contents

1 Antenna, complete with 5 m coax cable and 3 F connectors

1 Adjustable gain amplifier, with 2 outputs for 3 TV+1 Radio DAB and FM output, operating at 12 and 24 V DC

TELECO-CONNECT WING-LAN 11



ULTRA HD
4K

2G • 3G • 4G • 5G



SMA
Connector



Internet Antenna 2G-3G-4G-5G

+Omnidirectional TV Antenna + Radio



The **Wing-Lan 11** integrates an omnidirectional TV antenna for **DVBT/T2 digital terrestrial** and **DAB+** radio signals with a high-efficiency internet antenna for 2G-3G-4G-5G signals. When paired with the TELECO router, it sets up a **WLAN WIFI** hotspot for browsing the internet, streaming and watching your favourite programmes.



DVB-T2 HEVC DVB-T t d t TNT



Horizontal reception diagram

Channels: 5-12 / 21-48

Gain with amplifier:

CH 5-12 16 dB

CH 21-48 26 dB

Power supply: 12/24 Volt

Diameter: 38 cm

Height: 19,5 cm

Weight: 1,2 kg

Internet signals. Reception frequencies:

5G: 700(B28) MHz

4G LTE: 800(B20)

900(B8)

1800(B3)

2100(B1)

2600(B7) MHz

3G UMTS: 900/1800/2100 MHz

GSM: 900 / 1800 MHz

Includes:

1 Antenna with 5m DVBT/T2 coaxial cable, 5m SMA 2G-3G-4G-5G coaxial cable and 3 F connectors

1 Adjustable gain amplifier with 3 outputs for 3 TV+1 DAB and FM radio outputs, operating at 12 and 24 Vdc

TELECO HUB

central control unit via smart phone for motorhomes and caravans



Android iOS

TELECO HUB CONTROL CENTRE

- Power supply: 12 Volts (10-15 V DC)
- Max consumption: 300 mA
- SIM Card connector: Micro SIM card
- Number of phones that can be connected via Bluetooth: 4
- Auxiliary outputs: 2 clean contacts 10A 250Vac / 30V DC
- Inputs: 2 digital channels (internal voltage 6 Volts)
- Dimensions: 147x97x35 mm
- Weight: 200g

The ideal interface for using your smartphone to control your motorhome or caravan by means of a simple app.

It operates via **Bluetooth** when nearby, and via **SMS** from a distance. Operation via **Bluetooth** is completely free of charge, whereas **SMS** control requires the installation of a Micro SIM CARD (either contract or PAYG) in the Teleco HUB box.

What can you do with your smartphone?



Turn lights on or off.
Check the temperature inside the vehicle, the battery level and the drinking and waste water levels, or whether the door or the skylight is open or closed.

Remote-control closure of the Flatsat BT or Telesat BT antenna to prevent gusts of wind damaging it.

Switch the Telair air conditioner on/off and set the temperature.

Turn the TIG generator on/off

Battery management

Bluetooth

SMS




T-AMM10DAB Android multimedia Monitor



Android multimedia monitor. 10.1 inch screen with 2 DIN frame and built-in DAB receiver

Google's Android operating system offers the simplicity, practicality and performance needed to take your multimedia experience to the next level. The extremely thin, tilt-adjustable display allows easy installation on vehicles with a 2 DIN housing.



Features

- 1DIN chassis
- 10.1" QLED capacitive display
- Adjustable monitor
- FM-RDS/AM tuner
- Built-in DAB+ with FM service
- Wireless Apple Link
- Wireless Android Link
- 2 USB ports
- Network hotspot and Wi-Fi
- Online navigation
- 360° surround view (optional)
- Bluetooth hands-free
- Bluetooth A2DP streaming
- External microphone
- Multilingual system
- RGB lighting
- Customizable user interface background
- Internal 4x45-watt amplifier
- DSP with 64-band EQ
- 2 pre-amplified outputs (front and rear)
- 1 pre-amplified subwoofer output
- 1 auxiliary A/V input
- 1 rear camera input (AHD and CVBS formats)
- 1 front camera input (AHD and CVBS formats)
- Integrated programmable steering wheel controls



TA11 DAB (optional)

Specifications

- B2000S platform
- 8-core processor
- CPU speed: 2.5 GHz
- 4GB RAM
- 64GB ROM OS
- Android 13 operating system
- App downloads via the Google Play Store
- Boot time under 2 seconds
- Integrated GPS module (antenna included)
- Glass DAB antenna included
- Bluetooth 5.0
- 10" QLED display, 1920x1080
- DSP audio processor with 64-band EQ
- Video inputs compatible with 1080p (HD): 1920x1080



Maximum connectivity with the DAB receiver

T-CPA 70 DAB CARPLAY™

DAB+
Digital Audio Broadcasting



TA70 DAB
(optional)



6.8" monitor with CarPlay™, Android Auto™ and Online-Navigation

Ideal for all those who want full smartphone integration with their infotainment system.

The T-CPA70 DAB CarPlay™ lets users connect latest-generation smartphones via CarPlay™ and Android Auto™.

Complete with DAB/DAB+ receiver, Online Navigation, phone, music and much more.

Phone, music and other functions can be conveniently and securely voice-controlled.



T-CPA70 DAB CarPlay™ requires a DAB antenna

Functions

- AM/FM radio with RDS, TP and AF
- DAB/DAB+ radio
- USB memory reader on rear
- CarPlay™
- Android Auto™
- Bluetooth for hands-free conversations and contacts list
- Bluetooth audio streaming
- Video input for rear-view camera
- Compatible with multi-function steering-wheel (resistive interface)
- Dual red-white lighting

Specifications

- 2 ISO size (93 x 172 mm)
- 6.8" WVGA capacitive touchscreen
- Compatible audio formats: MP3/WMA/FLAC
- Compatible video formats: MPEG/AVI/DIVX/JPG
- Graphic equalizer
- Adjustment of subwoofer level and • cutoff frequency
- 4+1 PreOut
- Amplification 4x40 Watt



androidauto



VIDEO CAMERAS AND MONITORS FOR MOTORHOMES



TRC 14 CCD

Rear-view camera

- CCD SONY 1/4
- Wide-angle 110°
- High resolution
- dim infrared LEDs < 0.1 Lux
- Microphone
- Mirror function
- Heater function
- 20 m cable
- Silver or white casing
- Casing in anodized cast aluminium with P69K salt-resistant treatment



TRC 13S CCD

Rear-view camera with automatic shut-off

- Automatic motorized lens
- SONY colour CCD camera 1/3
- Wide-angle 130°
- dim infrared compensation LEDs < 0.1 Lux
- Microphone
- Mirror function
- Heating element with temperature control
- Electronic regulation of light intensity
- 20 m cable
- Casing in powder coated anodised cast aluminium protective cover and stainless steel bracket



TRCL CMOS

Side-view camera

- Wide-angle lens 130°
- High resolution
- Infra-red 0.5 Lux LEDs for night vision
- Microphone
- Adjustment angle on basis of vehicle characteristics
- Flexible support for normal rear view, support for reverse drive view, left and right side view
- Weather resistant IP67K casing, IP67K



TP7HR/2

High resolution 7" LCD monitor for 2 video cameras

- 7" TFT panel /16:9 800x480 pixels
- High brightness 1600 cd/m2
- Video input 1V ± 20%750hm
- Audio input 400mA/1W
- Audio output 1W
- Power Supply 12-32V DC
- Consumption in standby mode <50mA
- TV system PAL/NTSC
- Working temperature -15°C - +65°C
- Complete with:
 - Connecting cables
 - Support foot
 - Sunshade



TP7HR/4

High resolution 7" LCD monitor for 4 video cameras

- 7" TFT panel /16:9 800x480 pixels
- High brightness 1600 cd/m2
- Video input 1V ± 20%750hm
- Audio input 400mA/1W
- Audio output 1W
- Power Supply 12-32V DC
- Consumption in standby mode <50mA
- TV system PAL
- Working temperature -15°C - +65°C
- Complete with:
 - Connecting cables
 - Support foot
 - Sunshade




ENERGY EVERYWHERE

The comfort of your own home even on holiday

You don't have to worry about where you'll get the energy to run your air conditioner any more, or your hair dryer, or your satellite TV, if all the lights are on.

With the Telair line of generators, all of this is taken care of, wherever you want to stop with your motorhome!




GENERATORS

Technical specifications	Model	Engine	Alternator	Max. power	Distortion frequency	Starting	Noise level	
	TIG 6000B PETROL 230 Vac	Yamaha MZ300	Inverter	5,2 kW - 230V 10A / 13,5Vdc	50 Hz 1%	Electric	54-68 dBA (7m)	
	TIG 6000G GAS 230 Vac	Yamaha MZ300	Inverter	5 kW - 230V 10A / 13,5Vdc	50 Hz 1%	Electric	54-68 dBA (7m)	
	TIG 3100B PETROL 230 Vac	Yamaha MZ175	Inverter	2,7 kW - 230V 10A / 13,3Vdc	50 Hz 1%	Electric	52-60 dBA (7m)	
	INOX							
	TIG 3100G GAS 230 Vac	Yamaha MZ175 GAS	Inverter	2,7 kW - 230V 10A / 13,3Vdc	50 Hz 1%	Electric	52-60 dBA (7m)	
	INOX							
	TIG 3000D DIESEL 230 Vac	HATZ 1B20 V	Inverter	2,5 kW - 230V 10A / 13,3Vdc	50 Hz 1%	Electric	58-61 dBA (7m)	
	ENERGY 2510 G GAS 230 Vac	Yamaha MZ175 GAS	Sinchron 2 poles	2,5 kW - 230V 10A / 12Vdc	50 Hz 5%	Electric	58 dBA (7m)	
	ENERGY 2510B PETROL 230 Vac	Yamaha MZ175	Sinchron 2 poles	2,5 kW - 230V 10A / 13,3Vdc	50 Hz 5%	Electric Manual	58 dBA (7m)	
	ECOENERGY GAS 12 Vdc	TELAIR	-	25A / 12Vdc		Electric	51 dBA (7m)	

Max fuel consumption	Dimensions	Weight	Control panel with 5 m cable	Floor or chassis mounting	Teleco HUB CI-BUS	OPTION
0,47 kg /KW/h Petrol	34x65,5x46,5cm ▲ ► ▼	79 kg				 Teleco App
0,39 kg /KW/h Gas	34x65,5x46,5cm ▲ ► ▼	80 kg				
0,39 Kg /KW/h Petrol	27,5x51,5x39cm ▲ ► ▼	52 kg				 Teleco App
0,4 Kg /KW/h Gas	27,5x51,5x39cm ▲ ► ▼	53 kg				
0,34 kg /KW/h Diesel	41x58,5x46,5cm ▲ ► ▼	87 kg				 Teleco App
1,2 Kg/h Gas	29,5x55,5x38,5cm ▲ ► ▼	60 kg				ASP  Automatic Starter
1,2 Lt/h Petrol	29,5x55,5x38,5cm ▲ ► ▼	58 kg				
0,27 Kg/h Gas	56,5x38x25cm ▲ ► ▼	19 Kg				

TIG 6000 B Inverter Petrol Generator



 230 Vac

- Stainless steel hatch
- Removable interior
- 2 attachment systems
- Variable speed adjuster

The TIG 3000B is a new generation 230 V AC inverter generator powered by a petrol engine.

The rotation speed is commanded by a newly developed electronic variable speed system which functions with an extremely low noise level as well as greatly reduced average petrol consumption. Inverter technology provides a very stable flow of power by pure sine wave.


The modernly designed remote control panel with display provides the user with full information on generator operation: oil level checks, working temperature and power consumption with automatic engine cut-off if values do not correspond with standard values.

The generator can be set to manual or automatic mode (if it's also used as a battery charger). It also has a BOOST button which can be used when a temporary increase of power for a very high electric load is needed.


It also has a special interface which makes it possible to use the new Teleco-Hub App to switch the generator on/off and control it remotely using an iOS or Android smartphone.



Technical specifications	TIG 6000 B
Engine	YAMAHA MZ 300
Rotation speed	2400 - 3600 rpm
Max. power output	5,2 kW - 230V 10 A /13,5Vdc
Distortion Frequency	50 Hz 1%
Start-up	Electric
Noise level	54-68 dBA (7m)
Max fuel consumption	0,47 kg/kW/h
Dimensions	34,5x65,5x46,5 cm ↑ → ↗
Weight	79 kg.



TIG 6000 G Inverter Gas Generator



 230 Vac



- Stainless steel hatch
- Removable interior
- 2 attachment systems
- Variable speed adjuster

Technical specifications	TIG 6000 G
Engine	YAMAHA MZ 300
Rotation speed	2400 - 3600 rpm
Max. power output	5 kW - 230V 10 A / 13,5Vdc
Distortion Frequency	50 Hz 1%
Start-up	Electric
Noise level	54-68 dBA (7m)
Max fuel consumption	0,39 kg/kW/h
Dimensions	34,5x65,5x46,5 cm
Weight	80 kg.




The TIG 6000 G is a latest-generation 230 V AC inverter generator powered by a liquefied petroleum gas (LPG) engine.

The rotation speed is commanded by a newly developed electronic variable speed system which functions with an extremely low noise level as well as greatly reduced average petrol consumption. Inverter technology provides a highly stable power flow by pure sine wave.

The modernly designed remote control panel with display provides the user with full information on generator operation: oil level checks, working temperature and power consumption with automatic engine cut-off if values do not correspond with standard values.

The generator can be set to manual or automatic mode (if it's also used as a battery charger). It also has a BOOST button which can be used when a temporary increase of power for a very high electric load is needed.

It also has a special interface which makes it possible to use the new Teleco-Hub App to switch the generator on/off and control it remotely using an iOS or Android smartphone.




TIG 3100 B Inverter Petrol Generator





 230 Vac

- Stainless steel hatch
- Removable interior
- 2 attachment systems
- Variable speed adjuster

The TIG 3100B is a new generation 230 V AC inverter generator powered by a petrol engine. The rotation speed is commanded by a newly developed electronic variable speed system which functions with an extremely low noise level as well as greatly reduced average petrol consumption. Inverter technology provides a very stable flow of power by pure sine wave. The modernly designed remote control panel with display provides the user with full information on generator operation: oil level checks, working temperature and power consumption with automatic engine cut-off if values do not correspond with standard values. The generator can be set to manual or automatic mode (if it's also used as a battery charger). It also has a BOOST button which can be used when a temporary increase of power for a very high electric load is needed. It also has a special interface which makes it possible to use the new Teleco-Hub App to switch the generator on/off and control it remotely using an iOS or Android smartphone.



Technical specifications	TIG 3100 B
Engine	YAMAHA MZ 175
Rotation speed	2700 - 3900 rpm
Max. power output	2,7 kW - 230V 10 A /13,3Vdc
Distortion Frequency	50 Hz 1%
Start-up	Electric
Noise level	52-60 dBA (7m)
Max fuel consumption	0,39 kg/kW/h
Dimensions	27,5x51,5x39 cm 
Weight	52 kg.




TIG 3100 G Inverter Gas Generator



Boost

Graphic OLED Display



USB Port



230 Vac

- Stainless steel hatch
- Removable interior
- 2 attachment systems
- Variable speed adjuster

Technical specifications	TIG 3100 G
Engine	YAMAHA MZ 175
Rotation speed	2700 - 3900 rpm
Max. power output	2,7 kW - 230V 10 A / 13,3Vdc
Distortion Frequency	50 Hz 1%
Start-up	Electric
Noise level	52-60 dBA (7m)
Max fuel consumption	0,4 kg/kW/h
Dimensions	27,5x51,5x39 cm ↑ → ↘
Weight	53 kg.




The TIG 3100 G is a new-generation 230 V AC inverter generator powered by a GAS engine (LPG).

The rotation speed is commanded by a newly developed electronic variable speed system which functions at an extremely low noise level and greatly reduces average gas consumption. Inverter technology provides a very stable flow of power by pure sine wave.


The modernly designed remote control panel with display provides the user with full information on generator operation: oil level checks, working temperature and power consumption with automatic engine cut-off if values do not correspond with standard values.

The generator can be set to manual or automatic mode (if it's also used as a battery charger). It also has a BOOST button which can be used when a temporary increase of power for a very high electric load is needed.

It also has a special interface which makes it possible to use the new Teleco-Hub App to switch the generator on/off and control it remotely using an iOS or Android smartphone.



TIG 3000 D Inverter Diesel Generator



 230 Vac



- Stainless steel hatch
- Removable interior
- 2 attachment systems
- Variable speed adjuster



The TIG 3000 D is a new-generation 230 V AC inverter generator powered by a Diesel engine. The rotation speed is commanded by a newly developed electronic variable speed system which functions at an extremely low noise level and greatly reduces average diesel consumption. Inverter technology provides a very stable flow of power by pure sine wave. The modernly designed remote control panel with display provides the user with full information on generator operation: oil level checks, working temperature and power consumption with automatic engine cut-off if values do not correspond with standard values. The generator can be set to manual or automatic mode (if it's also used as a battery charger). It also has a BOOST button which can be used when a temporary increase of power for a very high electric load is needed. It also has a special interface which makes it possible to use the new Teleco-Hub App to switch the generator on/off and control it remotely using an iOS or Android smartphone.



Technical specifications	TIG 3000 D
Engine	HATZ 1B20 V
Rotation speed	2400 - 3200 rpm
Max. power output	2,5 kW - 230V 10 A /13,3Vdc
Distortion Frequency	50 Hz 1%
Start-up	Electric
Noise level	58-61 dBA (7m)
Max fuel consumption	0,34 kg/kW/h
Dimensions	41x58,5x46,5 cm ↑ → ↗
Weight	87 kg.





ENERGY 2510 G Gas Generator



 230 Vac

- Remote control panel
- Stainless steel hatch
- Removable interior
- 2 attachment systems




Option **ASP**
Automatic Starter Control Panel

Super-silent GAS generators with Yamaha engine, contained in a sound- proofed metal casing. Fully automatic electronic starting system complete with remote control panel with 5 m cable equipped with: total and partial hour counter, oil and gas level indicator lights, overheating indicator with automatic engine stop. Built-in battery charger, 12 Volts/10A. Pull out drawer for easy generator maintenance. 2 fixing system.

The ASP panel allows automatic power on/off if the generator is connected to a battery charger (230/12 Volt) with relative battery.

Technical specifications	Energy 2510 G
Engine	YAMAHA MZ 175
Rotation speed	Syncon
Max. power output	2,5 kW - 230V 10 A /12Vdc
Frequency	50 Hz
Start-up	Electric
Noise level	58 dBA (7m)
Max fuel consumption	0,8 kg/h
Dimensions	29,5x55,5x38,5 cm ↑ → ↘
Weight	60 kg

ENERGY 2510 G



ENERGY 2510 B Petrol Generator



 230 Vac



Option **ASP**
Automatic Starter Control Panel




- Remote control panel
- Stainless steel hatch
- Removable interior
- 2 attachment systems

Technical specifications	Energy 2510 B
Engine	YAMAHA MZ 175
Rotation speed	Syncron
Max. power output	2,5 kW - 230V 10 A /12Vdc
Frequency	50 Hz
Start-up	Electric / Manual
Noise level	58 dBA (7m)
Max fuel consumption	1,2 Lt/h
Dimensions	29,5x55,5x38,5 cm ↑ → ↗
Weight	60 kg.

Super-silent petrol generators with Yamaha engine, contained in a sound- proofed metal casing. Fully automatic electronic starting system complete with remote control panel with 5 m cable equipped with: total and partial hour counter, oil and petrol level indicator lights, overheating indicator with automatic engine stop. Built-in battery charger, 12 Volts/10A. Pull out drawer for easy generator maintenance.

The ASP panel allows automatic power on/off if the generator is connected to a battery charger (230/12 Volt) with relative battery.

ENERGY 2510 B



Accessories 230 V ac Generators



S15

15 L petrol and diesel tank, complete with filler and reserve indicator.



S15B

15 L petrol and diesel tank, complete with filler and reserve indicator.



SS15

Tank bracket.



SP15

Folding brackets for fuel tank attachment.



TB40

Ø 40mm petrol pipe connecting the S15 tank to petrol filler.



KTB

Petrol pipe kit for S15 tank



KTD

Diesel pipe kit for S15 tank



TB6 - TB7 - TB5

TB6 – pipe 6x12 for petrol
TB7 – 7x13 delivery pipe for diesel
TB5 – 5x 12 return pipe for diesel



RB

Petrol fuel tap with brackets



FB

Petrol filter



PEC

Electric fuel pump



FD

Diesel filter



MSE
Spacer box for control panel



CDR10 - CDR15
CDR10 - 10 m panel connecting cable
CDR15 - 15 m panel connecting cable



RELÈ 12V 200A
To temporarily connect the engine
battery and service battery



CR
Relay for automatic mains power / Energy
generator switchover.



RCB
Battery charge adjusting unit.



KMD
90° connecting pipe kit for diesel
generator



MAE/2
Additional muffler for petrol generator Energy
2510B and gas generator Energy 2510G.
Pipe length: 1 m dish



MAE/4
Additional muffler for petrol generator Energy
4010B and gas generator Energy 4010G.
Pipe length: 2 m



PM22 - PM30
PM 22 - Hose Ø 22 for additional muffler MAE/2
PM 30 - Hose Ø 30 for additional muffler MAE/4
and Diesel

ECOENERGY LITHIUM

Gas battery charger, ideal for the latest Lithium (LiFeP04) batteries.



TG 480 • TG 480 MEF • TG 600 MEF

12 Vdc - 480/600 A*

*480 / 600 A - Daily production



Very powerful: a battery charger with a charge capacity more than double that of a fuel cell or a 100 W solar panel
Fully automatic:
starts when the battery is running low (11.9 V) and stops when it is charged (14.5 V).
Quiet: thanks to thick soundproof insulation, there is a very low amount of emitted noise (only 51 dBA at 7 m) which is almost imperceptible.
Practical and ecological: just connect it to the gas cylinder already in your camper.
Remote control panel

ECOENERGY CONTROL PANEL

- 1 - Overheating and low oil level warning light
- 2 - ECOENERGY operation phases indicator light
- 3 - Automatic Start and Shutdown
- 4 - Forced Manual Start Button. Used if you wish to switch on the ECOENERGY even if battery voltage is above the minimum threshold of 11.9 Volt. When a voltage of 14.5 Volt is reached the ECOENERGY switches off the engine automatically and reverts to stand-by.

	SOLAR PANEL 100W/h	FUEL CELL 105 W/h	ECOENERGY TG480 240W/H



Technical specifications	ECOENERGY TG 480	ECOENERGY TG 480 MEF	ECOENERGY TG 600 MEF
Automatic operation	Start 11,9V Stop 14,5 V	Start 11,9V Stop 14,5 V	Start 11,9V Stop 14,5 V
Working temperature with propane gas	+50°C ÷ -25°C	+50°C ÷ -25°C	+50°C ÷ -25°C
Rated current A/h	20 A/h (480 A/24h)	20 A/h (480 A/24h)	25 A/h (480 A/24h)
LPG gas fuel	30 mBar ± 2	30 mBar ± 2	30 mBar ± 2
Gas Consumption/Hour	270 g/h	270 g/h	290 g/h
Lube oil consumption	1 Lt / 115 h	1 Lt / 115 h	1 Lt / 115 h
LpA 7 m noise level	51 dBA	51 dBA	52 dBA
Weight	19 Kg	19 Kg	19 Kg
Dimensions without brackets	565x380x250 mm	565x380x250 mm	565x380x250 mm
Recommended batteries	160 ÷ 300 Ah	160 ÷ 300 Ah	160 ÷ 300 Ah
Supplied current can be selected: fixed or variable	–	 	 
High altitude operation up to 2300 m	–		
Connection cable with control unit	5 m	5 m	5 m



Accessories for ECOEnergy and 12 V DC generators

Installation brackets



SMTG
90° mounting bracket.



SPTG
Floor fastening.



SSTG
Hung bracket.



SATG
Bracket for AL-KO frame.



KPTAG
Conversion KIT from SPTG to SATG.



KPSTG
Conversion KIT from SPTG to SSTG.



KESMTG
SMTG bracket extension KIT.

For lubrication

TGO 1000 - Description: 100% synthetic strawberry-scented special oil for 2-stroke engines.

It considerably reduces the emission of smoke and bad smell from the exhaust pipe, keeping the motor clean and always ready to start (0.45 l).



TGO 1000



SOR

Remote Oil tank kit.
Pipe length: 2.7 m

Switches, clamps and cables



SWTG

Disconnecting switch kit for TG 480 / TG 480 MEF / TG 600 MEF



MB3P

3-way multiple clamp for battery Positive Pole (+).



MB3N


3-way multiple clamp for battery Negative Pole (-).

Accessories for intake and exhaust gas



TSA50

Metal exhaust pipe, Ø 50. Standard length: 1 m dish





TSP57

Ø 57 PVC tube for hot air. Standard length: 10 m dish



MAG

Supplementary exhaust 450mm x 70mm




Gas pipes and couplings



RG8

K8x8 gas tap.



Other accessories



KSS

Start threshold kit (12.04 V; 12.18 V; 12.32 V).



KH

Hour counter kit.





Contacts

ITALY - TELECO SPA
Via E. Majorana 49
48022 LUGO (RA)
Tel. + 39 0545 25037
mail: info@telecogroup.com
www.telecogroup.com

DEUTSCHLAND - TELECO GmbH
82041 Deisenhofen
Tel. 089 21129976
telecogmbh@telecogroup.com
www.teleco-deutschland.de
Vertretung:
Zimmer
Ziegenhainer Str. 7 - 34626 Neukirchen
Tel. 06694-9108000
uwe.zimmer-saalbach@zimmer-automotive.de
TELECO SERVICE 08921129997
TELAIR SERVICE 08921129995

FRANCE - TELECO SAS
3, impasse des Iles - ZA La Maladiere
07300 St Jean de Muzols - France
contact@telecogroup.fr
www.telecogroup.fr

SERVICE TECHNIQUE
04 75 08 49 17 (appuyer sur 1)
ADMINISTRATION
04 75 08 49 17 (appuyer sur 2)

SERVICE COMMERCIAL :
EURO TECHNIQUE DIFFUSION
Jean-Philippe Bleys
Tel. 03 86 28 25 95
teleco.telair@bleysetd.com

In Europe

GREAT BRITAIN - SCAN TERIEUR LTD
30, The Metro Centre, Tolpits Lane - Watford,
Herts - England - WD18 9XG
Tel. 01923 800353
e-mail: info@scan-terieur.com
www.scan-terieur.com

THE NETHERLANDS/BELGIUM/LUXEMBOURG/
DENMARK/SWEDEN/ NORWAY/FINLAND - KARMAN
ACCESSOIRES
Telgterweg 275. 3853NJ ERMELO - Nederland
Tel. +31 (0) 341 722450
e-mail: info@karmanaccessories.com
www.karmanaccessories.com
Dealers and Service Partners: www.telecobenelux.eu

ESPAÑA
Servicio técnico: Fills de Rocha i Lopez, S.L.
Avd. Pau Casals, 132 - 08907 L'Hospitalet Llobregat
Barcelona - España
Tel. 933 333 753 - 933 348 071
fillsrocha@fillsrocha.com
www.fillsrocha.com
Servicio comercial : EURO TECHNIQUE DIFFUSION
Jean-Philippe Bleys
Tel. +33 (0)3 86 28 25 95
teleco.telair@bleysetd.com

www.telecogroup.com



TELECO - France



TELECO - Italy



**GERMAN
INNO
VATION
AWARD '24
WINNER**



**GERMAN
INNO
VATION
AWARD '22
WINNER**



Your Teleco
dealer: